

NRL Memorandum Report 1758**Copy No. 12 of 75 Copies**

Information on Over-the-Horizon Radar

Part XII - Missile Detection at Altitude for a Medium Distance

J. M. HEADRICK AND E. W. WARD

*Radar Techniques Branch
Radar Division*

and

D. L. LUCAS

*Bell Aerosystems Company
Tucson, Arizona*

formerly with

Institute for Telecommunication Sciences and Aeronomy
Department of Commerce
Environmental Science Services Administration

February 1967

DECLASSIFIED: By authority of
OPNAVINST 5510.1H, 29 APR 88
Cite Authority *C. ROGENS* Date *1221-1*
Entered by *NRL Code*



NAVAL RESEARCH LABORATORY
Washington, D.C.

Report Documentation Page			Form Approved OMB No. 0704-0188		
<p>Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p>					
1. REPORT DATE FEB 1967	2. REPORT TYPE	3. DATES COVERED 00-00-1967 to 00-00-1967			
4. TITLE AND SUBTITLE Information on Over-the-Horizon Radar, Part XII -Missile Detection at Altitude for a Medium Distance			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory, Washington, DC, 20375			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF: a. REPORT b. ABSTRACT c. THIS PAGE unclassified unclassified unclassified			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 74	19a. NAME OF RESPONSIBLE PERSON

UNCLASSIFIED

This document is classified [REDACTED] because it reveals proposed location of a new facility, the location of targets of interest and characteristics of an R and D equipment.

ABSTRACT
([REDACTED])

This report gives expected OTH radar performance for a site near Diyarbakir viewing the region around Lake Balkash.

PROBLEM STATUS

This is an interim report on a phase of the problem; work is continuing.

AUTHORIZATION

USAF MIPR (30-602) 64-3412 to the
Naval Research Laboratory
dated 26 March 1964
NRL Problem 53R02-42

MISSILE DETECTION AT ALTITUDE FOR A MEDIUM DISTANCE
(Unclassified Title)

INTRODUCTION

It has been suggested that a limited capability hf radar might be accommodated on the existing Turkish site near Diyarbakir and that this radar could furnish useful coverage for missiles in the Lake Balkash region (1, 2 and 3). The radar location is taken as $38^{\circ}\text{N } 40^{\circ}\text{E}$ and the target as $46^{\circ}\text{N } 73^{\circ}\text{E}$ giving a great circle ground range of 1494 naut mi and forward and reverse bearings of 061° and 262° true. ITSA long range ionospheric data have been used with the prediction methods of ESSA Technical Report, IER 1 - ITSA 2 and the radar application of such methods as is described in an NRL report (5). The operating period of 1968-1970 with an estimated average sunspot number (SSN) of 110 is examined for three months, June, September and December, being representative of summer, spring/fall and winter respectively. A frequency complement composed of narrow band channels at nominally 9, 10, 11, 12, 13, 14, 16, 18, 20, 22, 24, 27, 30 Mc has been assumed available. Target altitudes considered are 0, 50, 100 and 150 km. The signal absorbing layer has been considered slightly below 100 km. Since the radar installed on the existing site probably will not permit a full ground screen, a launch angle minimum of 4° has been set. This controlling noise was taken as that given in CCIR Report #322 except that noise power was not allowed to drop below a threshold set by a median level, $N_m = 148 + 12.6 \ln(fmc/3)\text{db}$, below a watt; this noise is an estimate for the narrow band (5-10 kc) frequency complement assumed.

RESULTS

The results are given in the form of diurnal graphs of % Time, S/N, Ψ and f .

% Time is a measure of radar effective operating time and also it is referred to as Total Reliability. In effect it is a combined reliability computed from individual reliabilities based upon the fading signal, fluctuating noise and probability of ionospheric support for the better frequencies in the complement. Implicit assumptions are that the radar is frequency and launch angle flexible, that existing propagation conditions are known and that the radar is properly operated.

S/N is the ratio in db of output signal-to-noise at the monthly median MUF.

Ψ is the vertical launch angle in degrees for the monthly median MUF path

f is the median MUF for the month given in megacycles per second. Time is given in hours GMT.

The modes considered are as sketched in Fig. 1, and on the diurnal graphs the mode for the median MUF is indicated. All percent time curves have been computed with the requirement that the output signal-to-noise be 10 db or better. The product (radiated power over a watt) (antenna gain over a free space isotrope)² (signal processing time over a second) (target radar area over a square meter) or $PG^2T\sigma$, has been taken as 143, 133, 123 and 113 db. As an example the $PG^2T\sigma = 143$ may be broken down as follows:

$P = 400$ kw average or	56 db
$G^2 =$	60 db
$T = 10$ sec. or	10 db
$\sigma = 50$ sq. meters or	<u>17 db</u> 143 db

An example of $PG^2T\sigma = 133$

$P = 400$ kw average or	56 db
$G^2 =$	50 db
$T = 10$ sec. or	10 db
$\sigma = 50$ sq. meters or	<u>17 db</u> 133 db

An example of $PG^2T\sigma = 123$

$P = 200$ kw average or	53 db
$G^2 =$	50 db
$T = 2$ sec. or	3 db
$\sigma = 50$ sq. meters or	<u>17 db</u> 123 db

Figures 2 through 13 are diurnal graphs of Total Reliability or Percent Time of effective operation (% Time), output median signal to median noise ratio (S/N) for the median MUF, launch angle (ψ) in degrees for the median MUF, and frequency (f) in megacycles per second for the median MUF. The median MUF mode is indicated between the % Time and S/N plots. These curves show a marked decrease in radar capability near midday 16^{cal} time (0900 GMT) for the summer months and equinoxes.

The effective operating times are summarized in Fig. 14 by daily average. The $PG^2T\sigma = 143$ table shows daily effective times of near 95%. With minor exceptions Fig. 14 shows more effective operating time for targets of 100 km and lower altitudes.

Figures 15, 16 and 17 give composite plots of S/N, the median MUF and its launch angle. For the years considered, an overall frequency span of 10 through 33 megacycles is required. Launch angles up to 11° are useful with indications that launch angles of less than 4° would also be useful if permitted. The modes, 1F 1F-, and 1F+ provide the coverage.

CONCLUSIONS

The problem under study is of missile skin tracking at about 1500 naut mi employing an AN/FPS-95 capability radar (6) but with frequency, azimuth sector and launch angle abbreviations. Some of the results are:

(a) The $PG^2T\sigma = 133$ db case corresponds to 400 kw average power (two AN/FPS-95 transmitters) and an assumed 10 seconds effective processing time against a 50 m^2 target. Effective operating time indicated is high at all altitudes, averaging over 80%.

(b) The $PG^2T\sigma = 123$ db case illustrates expected performance for a single AN/FPS-95 transmitter (200 kw) with 2 seconds of processing gain against a 50 m^2 target. Effective operating time averages over 50%.

(c) The exhibits for $PG^2T\sigma = 143$ and 113 db are given to show how even higher and lower performance radars can be expected to operate.

Examination of Figs. 15, 16, 17 shows that a single vertical beam covering 4° to 12° provides for all average vertical launch angles. These figures also show that provisions for radiation below 4° can significantly improve performance, principally at the 100 km target altitude but to some extent at the 150 km altitude.

A single beam AN/FPS-95 with a considerably abbreviated antenna can provide useful coverage.

PREDICTION EXPLANATION AND SET OF TABLES

The problem brief will be stated. The predictions were computer for June, September and December, sunspot number 110 using the following parameters:

- a. Height of target - (0, 50, 100 and 150 km)
- b. Gain of antenna - (25 db)
- c. Target radar area - ($SIGMA$) (1000 sq. meters). This area was a computational convenience to go with the noise tabulation which was in power in a 1-cps band. The specified parameter in fact is the (radar area) (integration time) product which would be $1000 \text{ m}^2 \text{ sec.}$
- d. 3 Mc/s manmade noise - (-148 dbw)

- e. Required signal-to-noise ratio - (0, 10, 20 and 30 db)
- f. Power - (200 kw)
- g. Minimum acceptable angle of takeoff and arrival - (4 degrees)

A description of the body of the printout follows:

1. MUF: Monthly median maximum usable frequency
2. MODE: The mode contributing most to the overall probability that at least one sky-wave path exists
3. ANGLE: The average takeoff and arrival angle associated with the above mode
4. C. PROB.: The overall probability that at least one mode is present to produce the quasi-minimum loss for the circuit
5. NOISE: The predominant noise (atmospheric, manmade or cosmic) (db < 1 watt in a 1-cps bandwidth)
6. F.S. LOSS: The free space loss between isotropic radiators (two-way)
7. P. LOSS: The propagation losses two way (ionospheric quasi-minimum and ground losses)
8. S/N - DB: The received signal power in the occupied bandwidth relative to noise in a 1-cps bandwidth
9. S/N PROB. A, B, C, and D: The probability that the available signal-to noise exceeds the required signal-to-noise, considering only the fluctuations of the signal and noise (ionospheric probability of support not included)

$$A, PG^2 T \sigma = 143 \text{ db}$$

$$B, PG^2 T \sigma = 133 \text{ db}$$

$$C, PG^2 T \sigma = 123 \text{ db}$$

$$D, PG^2 T \sigma = 113 \text{ db}$$

10. T. REL.: The total combined reliability of the frequency complement ($PG^2 T \sigma = 143, 133, 123 \text{ and } 113 \text{ db}$)

Computation results are shown in the following tables for $PG^2 T \sigma = 143, 133, 123 \text{ and } 113 \text{ db}$.

An approximate manual solution for one hour will be given. The relation used is $(S/N) = \frac{PG^2 T_0 \lambda^2}{NL(4\pi)^3 R^4}$

The computations were for $\sigma = 1000$ and $T = 1$, however, any $\sigma T = 1000$ is valid, and the examples in the body of the report were taken as $\sigma = 50 \text{ m}^2$ and $T = 20 \text{ sec}$. since 50 m^2 is an appropriate estimate of missile skin radar area and 20 sec. is approximately the maximum signal processing time that can be effective. Since the free space spreading loss as given in the table is

$$\text{F.S. LOSS} = \left(\frac{4\pi R}{\lambda} \right)^4$$

that is, the two-way spreading loss between two isotropes, the radar equation will be rearranged:

$$(S/N) = \frac{PG^2 T_0}{NL} \times \left(\frac{\lambda}{4\pi R} \right)^4 \times \frac{4\pi}{\lambda^2}$$

or using db

$$(S/N)_{db} = 10 \log P + 20 \log G + 10 \log \sigma T - 10 \log N - 10 \log L - \text{F.S. LOSS} - 10 \log \frac{\lambda^2}{4\pi}$$

The specified parameters set

$$10 \log P = 53$$

$$20 \log G = 50$$

$$10 \log \sigma T = 30$$

consider the case for June, 18 hours and 150 km altitude at the MUF.

$$-10 \log N = 169 \text{ from the table}$$

As a matter of interest this happened to be the median noise level set by specifying a rural noise threshold

$$10 \log L = 9 + 9$$

One factor is taken from the table and is the quasi-minimum loss plus ground reflection loss where appropriate. The other is the excess system loss which though not printed out in the table was used in the computations. The excess system loss is the factor that randomly varies giving the fluctuating signal description. Its median value for the problem here under study remained approximately 9 db at all times.

F.S. LOSS = 253 from the table

$$10 \log \frac{\lambda^2}{4\pi} \approx 13 \text{ at } 17.9 \text{ Mc/s}$$

$$\text{So } 53 + 50 + 30 + 169 - 9 - 9 - 253 - 13 = 18 \text{ db}$$

This compares with the 17 printed out in the table.

An example of determining Total Reliability (T. REL) or % Time of effectiveness will be given for the same time block for which the above output signal-to-noise ratio was computed. By inspection the highest best frequency of the complement is 14 Mc/s, and the reliability at that frequency can be computed

$$R_1 = (\text{C. PROB}) (\text{S/N PROB})$$

or using the

$$PG^2 T \sigma = 123$$

$$R_1 = (0.96)(0.42) = 0.40$$

Another reliability is computed selecting the best case from frequencies more than 15% above that of R_1 . This turns out to be at 18 Mc/s.

$$R_2 = (0.48)(0.42) = 0.20$$

Similarly a reliability is computed for the best case among frequencies at least 15% below that of R_1 . This is for 11 Mc/s and gives

$$R_3 = (0.99)(0.32) = 0.32$$

It has been assumed that these reliabilities from frequencies at least 15% apart are independent thus $T. REL. = R_1 + R_2 + R_3 - R_1 R_2 - R_1 R_3 - R_2 R_3 + R_1 R_2 R_3$
 $= 0.40 + 0.20 + 0.32 - 0.08 - 0.13 - 0.06 + 0.03 = 0.95 - .27 = 0.68$ or 68%.
This is what the computer printed out.

REFERENCES

1. General Electric Co., Memo on "Big Dee" Radar Program (U), G.E. Heavy Military Electronics Department, August 1966 Secret
2. General Electric Co., Big Dee Performance Analysis - Propagation Performance (U), G.E. Heavy Military Electronics Department, October 14, 1966 Secret
3. General Electric Co., Project Big Dee (U), G.E. Heavy Military Electronics Department, October 10, 1966 [REDACTED]
4. D.L. Lucas and G.W. Haydon, Predicting Statistical Performance Indexes for High Frequency Ionospheric Telecommunication Systems (U), ESSA Technical Report, IER 1 - ITSA 1, Department of Commerce, Environmental Science Services Administration, August 1966
5. J.M. Headrick, E.N. Zettle and D.L. Lucas, HF Sky Wave Radar Performance (U), Naval Research Laboratory Report to be published in 1967 [REDACTED]
6. F.E. Boyd, F.M. Gager, J.M. Headrick, G.K. Jensen, E. Lurker, LCDR, USN, G.A. Morgan, E.N. Zettle, Information on Over-the-Horizon Radar, Part II (U), NRL Memo Report June 1, 1965 [REDACTED]




Fig. 1 - The transmission modes considered for targets at altitudes greater than zero are sketched for F-layer reflection




Fig. 2 - Percent of time of effective operation for four values of $PG^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 3 - Percent of time of effective operation for four values of $\text{PG}^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $\text{PG}^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 4 - Percent of time of effective operation for four values of $PG^2 T_\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T_\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 5 - Percent of time of effective operation for four values of $PG^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 6 - Percent of time of effective operation for four values of $PG^2 T_\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T_\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 7 - Percent of time of effective operation for four values of $\text{PG}^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $\text{PG}^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 8 - Percent of time of effective operation for four values of $PG^2 T_\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T_\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 9 - Percent of time of effective operation for four values of $PG^2 T_\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T_\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 10 - Percent of time of effective operation for four values of $\text{PG}^2 T_\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $\text{PG}^2 T_\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 11 - Percent of time of effective operation for four values of $\text{PG}^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $\text{PG}^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 12 - Percent of time of effective operation for four values of $\text{PG}^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $\text{PG}^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours




Fig. 13 - Percent of time of effective operation for four values of $PG^2 T\sigma$, the median MUF (f) for the designated month in Mc/s, the signal-to-noise ratio (S/N) at the median MUF in db for $PG^2 T\sigma = 133$, the vertical launch angle (ψ) in degrees for the median MUF path, and the transmission mode for the median MUF path are given versus GMT hours

PERCENT TIME

$$PG^2 T_{\sigma} = 143$$

TARGET ALT.	JUNE	SEPT.	DEC.	YEAR
0 KM	94	96	94	95
50 KM	94	98	97	96
100 KM	89	98	96	94
150 KM	86	98	90	91

$$PG^2 T_{\sigma} = 133$$

0 KM	85	90	83	86
50 KM	84	93	94	90
100 KM	75	90	94	86
150 KM	66	86	84	79

$$PG^2 T_{\sigma} = 123$$

0 KM	61	68	56	62
50 KM	58	68	62	63
100 KM	51	62	68	60
150 KM	35	52	56	47

$$PG^2 T_{\sigma} = 113$$

0 KM	27	30	21	26
50 KM	26	29	23	26
100 KM	22	25	26	24
150 KM	11	18	19	16

Fig. 14 - Effective operating time is given by daily average




Fig. 15 - The median MUF, its launch angle and S/N versus GMT are shown for the month indicated as combined plots for the altitudes considered




Fig. 16 - The median MUF, its launch angle and S/N versus GMT are shown for the month indicated as combined plots for the altitudes considered




Fig. 17 - The median MUF, its launch angle and S/N versus GMT are shown for the month indicated as combined plots for the altitudes considered

1 JUN SSN= 110 26.015
 TRANSMITTER RECEIVER AZIMUTHS N.MILES
 SITE C RCVR 0 61.0 262.8 1493.7
 SIGMA= 1000 SQ. METERS ANT= 25DB
 OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
 PWR=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB
 OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30
2	19.6	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-
		76	62	52	49	48	49	50	55	63	75	75	-	-
		50	99	99	98	96	94	84	67	42	13	-	-	-
		98	97	96	96	96	96	96	97	98	98	-	-	-
		170	161	162	163	164	165	166	168	169	171	172	-	-
		255	241	243	244	246	247	249	251	253	255	257	-	-
		5	23	20	17	14	13	11	8	6	5	4	-	-
		21	2	5	8	11	13	15	18	20	22	23	-	-
		99	63	79	90	96	97	98	99	99	99	99	-	-
		95	23	33	45	60	71	80	89	94	96	97	-	-
		60	4	8	13	21	27	34	43	54	62	68	-	-
		21	0	0	2	3	5	8	13	18	22	25	-	-
4	22.4	1 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F
		68	179	173	172	175	182	60	49	50	55	65	65	65
		50	98	95	90	83	72	97	93	84	71	53	38	19
		97	101	101	101	101	101	97	96	96	96	97	97	97
		172	161	162	163	164	165	166	168	169	171	172	173	174
		257	242	244	245	247	248	249	251	253	255	257	258	260
		9	66	58	51	45	40	22	18	14	12	9	8	6
		18	-42	-33	-26	-20	-15	4	9	12	16	18	20	21
		99	0	0	9	2	7	75	91	97	99	99	99	99
		89	0	0	0	0	0	30	47	66	81	88	93	95
		44	0	0	0	0	0	7	15	24	35	43	51	60
		13	0	0	0	0	0	2	4	8	12	17	21	28
6	23.0	1 F	-	-	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F
		57	-	-	169	163	164	169	189	48	45	51	52	52
		50	-	-	91	84	74	62	38	87	75	59	43	23
		97	-	-	100	100	100	100	102	96	96	96	96	96
		172	-	-	163	164	165	166	168	169	171	172	173	174
		257	-	-	245	247	248	249	252	253	255	256	258	260
		13	-	-	69	62	55	49	39	21	17	14	12	10
		14	-	-	-44	-37	-29	-23	-13	6	10	13	16	18
		98	-	-	0	0	0	0	7	84	93	97	99	99
		76	-	-	0	0	0	0	0	36	50	68	82	90
		29	-	-	0	0	0	0	0	8	14	23	34	44
		5	-	-	0	0	0	0	0	0	1	3	7	11
8	22.8	1 F	-	-	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F
		57	-	-	179	170	168	172	188	55	49	53	51	51
		50	-	-	90	82	72	59	33	86	74	57	40	19
		97	-	-	101	100	100	101	102	96	96	96	96	96
		172	-	-	163	164	165	166	168	169	171	172	173	174
		257	-	-	245	247	248	249	252	253	255	256	258	260
		15	-	-	76	68	61	54	43	23	20	16	14	11
		13	-	-	-51	-43	-35	-28	-17	3	8	12	14	17
		97	-	-	0	0	0	0	3	71	88	96	98	99
		70	-	-	0	0	0	0	0	25	41	62	73	87
		25	-	-	0	0	0	0	0	4	10	20	27	40
		4	-	-	0	0	0	0	0	0	1	3	4	9

		OPERATING FREQUENCIES																
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30				
10	22.1	1 F	-	2 F	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	-	MODE		
		68	-	195	185	182	186	196	209	59	59	68	63	63	-	ANGLE		
		50	-	94	88	79	68	54	28	83	68	51	34	14	-	C.PROB.		
		97	-	102	102	101	102	102	97	97	97	97	97	97	-	DELAY		
		172	-	162	163	164	165	166	168	169	171	172	173	174	-	NOISE		
		257	-	244	245	247	248	250	252	253	255	257	258	260	-	FS.LOSS		
		14	-	79	70	62	55	49	40	21	18	14	12	10	-	P. LOSS		
		13	-	-54	-46	-37	-30	-23	-14	5	10	13	15	18	-	S/N..DB		
		97	-	0	0	0	0	0	6	80	93	97	98	99	-	S/N..PROB.A		
		68	-	0	0	0	0	0	0	32	50	68	78	90	-	S/N..PROB.B		
		23	-	0	0	0	0	0	0	6	14	23	31	44	-	S/N..PROB.C		
		3	-	0	0	v	0	0	0	0	1	3	6	11	-	S/N..PROB.D		
12	21.2	1 F	2 F	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	-	MODE		
		70	191	182	181	184	193	211	57	56	62	66	66	-	ANGLE			
		50	98	95	89	79	64	47	93	82	63	40	19	-	C.PROB.			
		97	102	101	101	101	102	104	97	96	97	97	97	-	DELAY			
		171	161	162	163	164	165	166	168	169	171	172	173	-	NOISE			
		256	242	244	245	247	248	250	251	253	255	257	258	-	FS.LOSS			
		11	73	64	56	50	44	39	20	16	13	11	9	-	P. LOSS			
		15	-49	-40	-32	-25	-19	-13	6	10	14	17	19	-	S/N..DB			
		99	0	0	0	0	3	10	82	94	98	99	99	-	S/N..PROB.A			
		80	0	0	0	0	0	1	36	54	72	85	91	-	S/N..PROB.B			
		34	0	0	0	0	0	0	9	18	28	39	47	-	S/N..PROB.C			
		8	0	0	0	0	0	0	1	3	6	10	15	-	S/N..PROB.D			
14	21.2	1 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	MODE		
		64	163	163	167	49	44	42	43	47	55	62	62	-	ANGLE			
		50	99	96	91	99	99	98	93	82	64	40	19	-	C.PROB.			
		97	100	100	100	96	96	96	96	96	97	97	97	-	DELAY			
		171	159	160	161	163	165	166	168	169	171	172	173	-	NOISE			
		256	242	243	245	246	247	249	251	253	255	257	258	-	FS.LOSS			
		6	49	42	37	19	17	15	12	9	7	6	5	-	P. LOSS			
		20	-26	-19	-14	4	8	11	15	17	20	21	23	-	S/N..DB			
		99	0	2	7	76	90	95	98	99	99	99	99	-	S/N..PROB.A			
		94	0	0	0	28	42	60	78	87	93	95	97	-	S/N..PROB.B			
		54	0	0	0	5	10	21	32	41	50	57	68	-	S/N..PROB.C			
		18	0	0	0	0	1	3	7	11	16	19	25	-	S/N..PROB.D			
16	21.8	1 F	2 F	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	-	MODE		
		66	156	160	165	172	182	196	40	46	53	65	65	-	ANGLE			
		50	99	99	98	92	81	62	98	92	74	46	20	-	C.PROB.			
		97	99	100	100	101	101	103	96	96	96	97	97	-	DELAY			
		172	158	160	162	164	165	166	168	169	171	172	173	-	NOISE			
		256	242	243	245	247	248	250	251	253	255	257	258	-	FS.LOSS			
		2	21	19	18	17	17	16	3	3	2	2	1	-	P. LOSS			
		26	0	3	5	7	8	8	23	24	25	26	26	-	S/N..DB			
		99	54	73	83	91	90	90	99	99	99	99	99	-	S/N..PROB.A			
		99	14	23	30	39	45	45	97	98	98	99	99	-	S/N..PROB.B			
		81	1	3	5	8	14	13	69	76	77	82	82	-	S/N..PROB.C			
		35	0	0	0	0	2	1	26	30	31	35	36	-	S/N..PROB.D			

		OPERATING FREQUENCIES																	
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30					
18	20.2	1 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	MODE		
		74	173	178	41	42	44	46	51	58	71	74	74	-	-	-	ANGLE		
		50	99	98	99	99	99	99	95	81	54	24	7	-	-	-	C.PROB.		
		97	101	101	96	96	96	96	97	97	97	97	97	-	-	-	DELAY		
		171	158	161	163	164	165	166	168	169	171	172	173	-	-	-	NOISE		
		255	242	244	244	246	247	249	251	253	255	257	258	-	-	-	FS.LOSS		
		1	18	17	5	4	3	3	2	2	1	1	1	-	-	-	P. LOSS		
		26	3	6	20	21	22	23	24	25	26	26	27	-	-	-	S/N..DB		
		99	74	87	99	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A		
		99	25	34	97	96	97	97	98	99	99	99	99	-	-	-	S/N..PROB.B		
		82	4	7	54	60	66	70	74	80	81	82	85	-	-	-	S/N..PROB.C		
		37	0	0	16	23	26	29	31	35	36	37	40	-	-	-	S/N..PROB.D		
20	18.9	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	MODE		
		78	43	44	46	48	50	52	59	70	78	78	78	-	-	-	ANGLE		
		50	99	99	99	99	98	95	83	61	29	6	-	-	-	C.PROB.			
		98	96	96	96	96	96	96	97	97	98	98	98	-	-	-	DELAY		
		170	159	162	163	164	165	166	168	169	171	172	172	-	-	-	NOISE		
		254	241	243	244	246	247	249	251	253	255	257	257	-	-	-	FS.LOSS		
		1	6	5	4	4	3	3	2	2	1	1	1	-	-	-	P. LOSS		
		25	16	19	20	21	22	23	24	25	26	26	26	-	-	-	S/N..DB		
		99	99	99	99	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A		
		98	87	95	94	96	97	97	98	99	99	99	99	-	-	-	S/N..PROB.B		
		78	35	46	54	60	66	70	74	80	81	82	85	-	-	-	S/N..PROB.C		
		34	8	13	21	23	26	29	31	35	36	37	37	-	-	-	S/N..PROB.D		
22	17.4	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	MODE		
		84	50	51	53	55	58	61	71	84	84	84	84	-	-	-	ANGLE		
		50	99	99	99	98	95	89	69	37	8	-	-	-	-	C.PROB.			
		98	96	96	96	96	97	97	97	98	98	98	98	-	-	-	DELAY		
		169	161	162	163	164	165	166	168	169	171	171	171	-	-	-	NOISE		
		253	241	243	244	246	247	249	251	253	255	255	255	-	-	-	FS.LOSS		
		1	6	5	4	4	3	3	2	2	2	1	1	-	-	-	P. LOSS		
		25	18	19	20	21	22	23	24	24	24	26	26	-	-	-	S/N..DB		
		99	99	99	99	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A		
		98	91	92	94	96	97	97	98	98	98	99	99	-	-	-	S/N..PROB.B		
		78	42	48	54	60	66	70	74	76	81	-	-	-	-	S/N..PROB.C			
		34	11	18	21	23	26	29	31	32	36	-	-	-	-	S/N..PROB.D			
24	15.9	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	MODE		
		86	52	54	56	59	63	68	86	86	86	86	86	-	-	-	ANGLE		
		50	99	98	95	90	83	74	47	11	-	-	-	-	-	C.PROB.			
		98	96	96	96	97	97	97	98	98	-	-	-	-	-	DELAY			
		168	161	162	163	164	165	166	168	169	-	-	-	-	-	NOISE			
		251	241	243	244	246	247	249	251	253	-	-	-	-	-	FS.LOSS			
		1	6	5	4	4	3	3	2	2	-	-	-	-	-	P. LOSS			
		24	18	19	20	21	22	23	24	24	-	-	-	-	-	S/N..DB			
		99	99	99	99	99	99	99	99	99	-	-	-	-	-	S/N..PROB.A			
		98	89	92	94	96	97	97	98	98	-	-	-	-	-	S/N..PROB.B			
		73	43	48	54	60	66	70	74	76	-	-	-	-	-	S/N..PROB.C			
		29	13	15	18	21	24	27	29	30	-	-	-	-	-	S/N..PROB.D			

[REDACTED]

1 JUN SSN= 110 26.915
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C RCVR 0 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0DB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	96	66	22	10	83	52	22	3	18	99	99	96	59
4	96	86	49	14	12	92	71	32	6	20	99	99	93	56
6	89	69	29	5	14	99	94	60	21	22	99	99	92	49
8	80	60	22	3	16	99	99	84	41	24	99	99	89	44

JUN SSN= 110 26.015

TRANSMITTER SITE C	RECEIVER RCVR 50	AZIMUTHS 61.0 262.8	N.MILES 1493.7
SIGMA= 1000 SQ. METERS			ANT= 25DB
OFF AZIMUTH 0 DEG.	MIN. ANGLE= 4 DEG.	OFF AZIMUTH 0 DEG.	
PWR=200.00KW	3 MC/S MAN.NOISE= -148 DBW	REQ.S/N= 0, 10, 20, 30DB	
OPERATING FREQUENCIES			
GMT	MUF	9 10 11 12 13 14 16 18 20 22 24 27 30	
2	20.5	1F- 1F- 1F+ 1F+ 1F+ 1F+ 1F- 1F- 1F- 1F- 1F- - -	MODE
	64	53 44 59 59 60 62 42 49 60 63 63 - -	ANGLE
	50	99 99 99 97 95 91 88 74 55 25 6 - -	C.PROB.
	97	96 96 97 97 97 96 96 97 97 97 - -	DELAY
	171	161 162 163 164 165 166 168 169 171 172 173 - -	NOISE
	255	241 243 244 246 247 249 251 253 255 257 258 - -	FS.LOSS
	5	24 20 21 18 17 15 9 7 5 4 4 - -	P. LOSS
	22	1 4 4 6 9 10 18 20 22 23 24 - -	S/N..DB
	99	58 75 76 84 92 94 99 99 99 99 99 - -	S/N..PROB.A
	96	20 30 30 38 49 54 89 94 96 97 98 - -	S/N..PROB.B
	63	3 6 7 10 16 18 43 54 62 68 73 - -	S/N..PROB.C
	23	0 0 0 1 2 3 13 18 22 25 29 - -	S/N..PROB.D
4	23.5	1F- 2F- 2F- 2F- 2F- 1F+ 1F+ 1F- 1F- 1F- 1F- - -	MODE
	56	174 165 163 165 170 66 60 62 40 47 53 53 53 -	ANGLE
	50	98 96 92 85 76 96 90 79 78 63 46 26 12	C.PROB.
	96	101 100 100 100 97 97 97 96 96 96 96 96 96	DELAY
	173	161 162 163 164 165 166 168 169 171 172 173 174 175	NOISE
	258	242 243 245 247 248 249 251 253 255 256 258 260 262	FS.LOSS
	8	67 59 52 46 41 26 22 18 12 10 8 7 5 -	P. LOSS
	20	-43 -35 -27 -21 -15 0 5 8 15 18 20 21 23 -	S/N..DB
	99	0 0 0 2 7 49 78 90 98 99 99 99 99 -	S/N..PROB.A
	93	0 0 0 0 0 16 32 45 77 88 93 95 97 -	S/N..PROB.B
	50	0 0 0 0 0 2 7 13 31 43 51 60 67 -	S/N..PROB.C
	16	0 0 0 0 0 0 0 2 7 12 17 21 24 -	S/N..PROB.D
6	24.3	1F- - 2F+ 2F- 2F- 2F- 2F- 1F+ 1F+ 1F- 1F+ 1F+ -	MODE
	43	- 184 165 156 153 157 177 58 59 70 42 65 65 -	ANGLE
	5	- 94 93 87 78 67 42 82 68 50 52 16 6	C.PROB.
	96	- 102 100 99 99 99 101 97 97 97 96 97 97	DELAY
	173	- 162 163 164 165 166 168 169 171 172 173 174 175	NOISE
	258	- 244 245 246 248 249 252 253 255 257 258 260 262	FS.LOSS
	12	- 88 70 63 57 50 40 25 21 18 12 14 13 -	P. LOSS
	16	- 63 -45 -38 -31 -24 -14 2 6 9 16 14 16 -	S/N..DB
	99	- 0 0 0 0 0 6 66 81 91 99 98 99 -	S/N..PROB.A
	82	- 0 0 0 0 0 0 22 34 46 82 75 81 -	S/N..PROB.B
	35	- 0 0 0 0 0 0 3 7 12 34 28 33 -	S/N..PROB.C
	7	- 0 0 0 0 0 0 0 0 1 7 5 7 -	S/N..PROB.D
8	24.1	1F- - - 2F+ 2F- 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F- 1F+ -	MODE
	44	- - 184 163 158 160 175 64 62 64 43 64 -	ANGLE
	50	- - 88 85 76 64 38 81 66 47 51 12 -	C.PROB.
	96	- - 101 100 100 100 101 97 97 97 96 97 -	DELAY
	173	- - 163 164 165 166 168 169 171 172 173 174 -	NOISE
	258	- - 245 247 248 249 252 253 255 257 258 260 -	FS.LOSS
	14	- - 86 69 62 56 44 27 23 20 14 15 -	P. LOSS
	14	- - 61 -44 -37 -30 -18 0 4 7 14 12 -	S/N..DB
	98	- - 0 0 0 0 2 49 72 85 98 96 -	S/N..PROB.A
	73	- - 0 0 0 0 0 14 26 38 73 65 -	S/N..PROB.B
	27	- - 0 0 0 0 0 1 4 8 27 22 -	S/N..PROB.C
	4	- - 0 0 0 0 0 0 0 0 4 3 -	S/N..PROB.D

		OPERATING FREQUENCIES																
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30				
10	23.2	1F-	-	2F+	2F-	2F-	2F-	1F+	1F-	MODE								
		56	-	199	178	173	175	181	76	50	45	49	50	50	50	ANGLE		
		50	-	93	90	82	72	59	89	88	76	61	44	22	8	C.PROB.		
		96	-	103	101	101	101	98	96	96	96	96	96	96	96	DELAY		
		172	-	162	163	164	165	166	168	169	171	172	173	174	175	NOISE		
		257	-	244	245	247	248	249	251	253	255	256	258	260	262	FS.LOSS		
		13	-	90	72	64	57	50	30	22	19	15	13	10	8	P. LOSS		
		14	-	-65	-47	-39	-31	-24	-3	4	9	12	15	18	20	S/N..DB		
		98	-	0	0	0	0	0	35	76	90	96	98	99	99	S/N..PROB.A		
		76	-	0	0	0	0	0	7	29	46	62	78	90	93	S/N..PROB.B		
		29	-	0	0	0	0	0	0	5	12	20	31	44	50	S/N..PROB.C		
		5	-	0	0	0	0	0	0	0	1	3	6	11	14	S/N..PROB.D		
12	22.3	1F-	2F-	2F-	2F-	2F-	2F-	1F+	1F-	-	MODE							
		58	187	175	171	173	179	75	49	44	47	56	54	54	54	-	ANGLE	
		50	99	96	91	83	69	97	96	88	73	53	30	8	-	C.PROB.		
		97	102	101	100	101	101	98	96	96	96	96	96	96	96	-	DELAY	
		172	161	162	163	164	165	166	168	169	171	172	173	174	-	NOISE		
		257	242	244	245	247	248	249	251	253	255	257	258	260	-	FS.LOSS		
		11	74	66	58	51	45	29	21	17	14	11	10	8	-	P. LOSS		
		17	-50	-41	-33	-26	-20	-3	6	9	14	16	18	20	-	S/N..DB		
		99	0	0	0	0	2	37	82	92	98	99	99	99	-	S/N..PROB.A		
		86	0	0	0	0	0	10	36	49	72	82	88	94	-	S/N..PROB.B		
		40	0	0	0	0	0	1	9	16	28	35	43	54	-	S/N..PROB.C		
		11	0	0	0	0	0	0	1	2	6	9	12	18	-	S/N..PROB.D		
14	22.3	1F-	2F-	2F-	1F+	1F-	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	-	MODE		
		52	154	153	65	42	53	53	55	61	73	50	50	50	-	ANGLE		
		50	99	97	99	99	99	97	90	75	53	53	30	8	-	C.PROB.		
		96	99	99	97	96	96	96	96	97	97	96	96	96	-	DELAY		
		172	159	160	161	163	165	166	168	169	171	172	173	174	-	NOISE		
		257	241	243	245	246	247	249	251	253	255	256	258	260	-	FS.LOSS		
		6	50	43	26	20	21	19	16	14	13	6	5	4	-	P. LOSS		
		21	-27	-20	-3	4	4	7	11	13	15	21	22	24	-	S/N..DB		
		99	0	2	37	76	75	87	95	97	98	99	99	99	-	S/N..PROB.A		
		95	0	0	9	28	27	41	57	71	77	95	96	98	-	S/N..PROB.B		
		58	0	0	0	5	4	11	20	27	31	57	63	75	-	S/N..PROB.C		
		20	0	0	0	0	0	1	3	5	7	19	22	30	-	S/N..PROB.D		
16	22.8	1F-	1F+	1F-	1F-	-	MODE											
		54	42	43	44	45	46	48	52	59	70	48	54	54	-	ANGLE		
		50	99	99	99	99	99	99	97	86	62	62	34	7	-	C.PROB.		
		96	96	96	96	96	96	96	97	97	96	96	96	96	-	DELAY		
		172	158	160	162	164	165	166	168	169	171	172	173	174	-	NOISE		
		257	241	243	244	246	247	249	251	253	255	256	258	260	-	FS.LOSS		
		2	13	11	10	9	8	8	7	7	7	2	2	1	-	P. LOSS		
		26	9	11	14	16	17	18	19	19	20	26	26	27	-	S/N..DB		
		99	94	97	99	99	99	99	99	99	99	99	99	99	-	S/N..PROB.A		
		99	48	60	79	88	87	90	91	92	93	99	99	99	-	S/N..PROB.B		
		83	12	17	27	35	41	45	47	49	50	82	82	87	-	S/N..PROB.C		
		37	1	1	4	6	12	13	15	16	16	35	36	41	-	S/N..PROB.D		

		OPERATING FREQUENCIES														
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30		
18	21.2	1F-	1F+	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	1F-	-	-	MODE	
		62	49	50	51	53	55	57	63	44	53	62	62	-	-	ANGLE
		50	99	99	99	99	99	99	92	89	67	38	14	-	-	C.PROB.
		97	96	96	96	96	96	97	96	96	97	97	97	-	-	DELAY
		171	158	161	163	164	165	166	168	169	171	172	173	-	-	NOISE
		256	241	243	244	246	247	249	251	253	255	257	258	-	-	FS.LOSS
		1	10	9	8	8	7	7	7	2	1	1	1	-	-	P. LOSS
		26	11	14	16	17	18	18	19	25	26	26	27	-	-	S/N..DB
		99	98	99	99	99	99	99	99	99	99	99	99	-	-	S/N..PROB.A
		99	61	77	89	87	90	90	91	99	99	99	99	-	-	S/N..PROB.B
		84	19	26	36	42	45	45	47	80	81	82	85	-	-	S/N..PROB.C
		38	2	4	8	14	16	16	17	35	36	37	40	-	-	S/N..PROB.D
20	19.7	1F-	1F+	1F+	1F+	1F+	1F-	1F-	1F-	1F-	1F-	1F-	-	-	MODE	
		67	53	55	56	58	61	41	46	54	67	67	-	-	ANGLE	
		50	99	99	99	98	96	97	89	71	45	15	-	-	C.PROB.	
		97	96	96	97	97	96	96	96	97	97	97	-	-	DELAY	
		170	159	162	163	164	165	166	168	169	171	172	-	-	NOISE	
		255	241	243	244	246	247	249	251	253	255	257	-	-	FS.LOSS	
		1	10	9	9	8	8	3	2	2	1	1	-	-	P. LOSS	
		25	12	15	16	17	17	23	24	25	26	26	-	-	S/N..DB	
		99	98	99	99	99	99	99	99	99	99	99	-	-	S/N..PROB.A	
		99	66	83	84	87	87	97	98	99	99	99	-	-	S/N..PROB.B	
		80	21	31	38	42	42	70	74	80	81	82	-	-	S/N..PROB.C	
		36	3	6	12	14	14	29	31	35	36	37	-	-	S/N..PROB.D	
22	18.1	1F-	1F+	1F-	-	-	MODE									
		73	60	41	42	44	47	49	57	72	73	-	-	-	ANGLE	
		50	99	99	99	98	97	93	77	52	17	-	-	-	C.PROB.	
		97	97	96	96	96	96	96	96	97	97	-	-	-	DELAY	
		169	161	162	163	164	165	166	168	169	171	-	-	-	NOISE	
		253	241	243	244	246	247	249	251	253	255	-	-	-	FS.LOSS	
		2	11	5	5	4	3	3	2	2	1	-	-	-	P. LOSS	
		24	14	19	20	21	22	23	24	25	26	-	-	-	S/N..DB	
		99	99	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A	
		98	75	92	94	96	97	97	98	99	99	-	-	-	S/N..PROB.B	
		76	28	48	54	60	66	70	74	80	81	-	-	-	S/N..PROB.C	
		32	5	18	21	23	26	29	31	35	36	-	-	-	S/N..PROB.D	
24	16.6	1F-	1F-	1F-	1F-	1F-	1F-	1F-	1F-	1F-	-	-	-	-	MODE	
		75	41	43	45	48	51	55	68	75	-	-	-	-	ANGLE	
		50	99	98	96	93	88	80	58	22	-	-	-	-	C.PROB.	
		98	96	96	96	96	96	96	97	98	-	-	-	-	DELAY	
		168	161	162	163	164	165	166	168	169	-	-	-	-	NOISE	
		252	241	243	244	246	247	249	251	253	-	-	-	-	FS.LOSS	
		2	7	5	5	4	3	3	2	2	-	-	-	-	P. LOSS	
		24	18	19	20	21	22	23	24	25	-	-	-	-	S/N..DB	
		99	99	99	99	99	99	99	99	99	-	-	-	-	S/N..PROB.A	
		98	89	92	94	96	97	97	98	99	-	-	-	-	S/N..PROB.B	
		76	4	48	54	60	66	70	74	80	-	-	-	-	S/N..PROB.C	
		3	13	15	18	21	24	27	29	34	-	-	-	-	S/N..PROB.D	

[REDACTED]

Z JUN SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C RCVR 50 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0UB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	95	60	21	10	89	64	25	4	18	99	99	90	51
4	97	85	47	14	12	95	78	38	8	20	99	99	92	53
6	79	60	24	3	14	99	87	48	16	22	99	99	92	54
8	74	48	17	2	16	99	99	76	36	24	99	99	89	47

3 JUN SSN= 110 26.015

TRANSMITTER SITE C	RECEIVER HCVR 100	AZIMUTHS 61.0 262.8	N.MILES 1493.7
SIGMA= 1000 SQ. METERS		ANT= 25DB	
OFF AZIMUTH 0 DEG.	MIN. ANGLE= 4 DEG.	OFF AZIMUTH 0 DEG.	
PWR=200.00KW	3 MC/S MAN.NOISE= -148 DBW	REQ.S/N= 0, 10, 20, 30DB	
OPERATING FREQUENCIES			
GMT	MUF	9 10 11 12 13 14 16 18 20 22 24 27 30	
2	21.5	1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F- 1F- 1F- 1F- 1F-	- - - MODE
	52	75 70 69 69 70 73 81 98 42 51 51	- - - ANGLE
	50	99 99 98 96 93 88 72 50 65 42 15	- - - C.PROB.
	94	98 97 97 97 97 97 98 99 93 94 94	- - - DELAY
	171	161 162 163 164 165 166 168 169 171 172 173	- - - NOISE
	256	241 243 245 246 248 249 251 253 254 256 258	- - - FS.LOSS
	2	27 24 21 18 17 15 14 13 3 2 2	- - - P. LOSS
	25	-2 1 4 6 8 10 13 13 25 26 26	- - - S/N..DB
	99	39 59 76 84 90 94 97 97 99 99 99	- - - S/N..PROB.A
	99	11 20 30 38 45 54 69 71 98 99 99	- - - S/N..PROB.B
	81	1 3 7 10 14 18 26 27 77 82 82	- - - S/N..PROB.C
	34	0 0 0 1 2 3 5 5 31 35 36	- - - S/N..PROB.D
4	24.7	1F- 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F- 1F-	MODE
	43	170 158 154 154 80 73 71 75 86 89 89 40 40	ANGLE
	50	98 97 93 88 97 95 87 73 55 38 23 35 18	C.PROB.
	94	100 99 99 99 98 97 97 98 98 98 98 93 93	DELAY
	173	161 162 163 164 165 166 168 169 171 172 173 174 175	NOISE
	258	242 243 245 246 248 249 251 253 255 257 258 260 261	FS.LOSS
	4	54 48 43 38 29 26 22 19 16 15 14 3 3	P. LOSS
	24	-29 -23 -17 -12 -3 0 5 8 11 12 14 25 27	S/N..DB
	99	0 1 4 12 38 49 78 90 94 96 98 99 99	S/N..PROB.A
	98	0 0 0 1 10 16 32 45 56 62 73 98 99	S/N..PROB.B
	75	0 0 0 0 1 2 7 13 19 22 29 80 84	S/N..PROB.C
	30	0 0 0 0 0 0 0 2 3 4 6 33 38	S/N..PROB.D
6	21.0	1F+ - 2F+ 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ -	MODE
	81	- 191 182 149 143 144 75 69 75 78 78 78	ANGLE
	5	- 93 88 89 82 72 89 77 59 42 27 11	C.PROB.
	98	- 102 101 99 98 98 98 97 98 98 98 98	DELAY
	171	- 162 163 164 165 166 168 169 171 172 173 174	NOISE
	256	- 244 245 246 248 249 251 253 255 257 258 260	FS.LOSS
	2	- 87 78 51 46 41 29 24 21 19 17 14	P. LOSS
	7	- -62 -53 -25 -20 -15 -2 2 6 9 11 13	S/N..DB
	87	- 0 0 0 1 5 39 66 81 91 95 97	S/N..PROB.A
	40	- 0 0 0 0 0 9 22 34 46 57 70	S/N..PROB.B
	9	- 0 0 0 0 0 0 3 7 12 17 25	S/N..PROB.C
	6	- 0 0 0 0 0 0 0 0 1 2 4	S/N..PROB.D
6	20.7	1F+ - - 2F+ 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ -	MODE
	81	- - 190 160 150 148 164 73 77 77 77 77	ANGLE
	50	- - 86 88 80 69 44 75 57 38 23 8	C.PROB.
	98	- - 102 99 99 99 100 97 98 98 98 98	DELAY
	171	- - 163 164 165 166 168 169 171 172 173 174	NOISE
	256	- - 245 247 248 249 252 253 255 257 258 260	FS.LOSS
	22	- - 85 55 50 46 37 27 23 20 18 16	P. LOSS
	5	- - -60 -30 -25 -19 -10 0 4 7 9 12	S/N..DB
	79	- - 0 0 0 2 13 49 72 85 91 96	S/N..PROB.A
	31	- - 0 0 0 0 1 14 26 38 47 65	S/N..PROB.B
	6	- - 0 0 0 0 0 1 4 8 13 22	S/N..PROB.C
	0	- - 0 0 0 0 0 0 0 0 1 3	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
10	24.5	-	2F+	2F-	2F-	2F-	2F-	1F+	- MODE						
	43	-	255	172	164	164	168	83	80	90	87	87	87	87	- ANGLE
	50	-	92	91	85	75	64	85	70	51	33	18	5	5	- C.PROB.
	93	-	103	100	100	100	100	98	98	98	98	98	98	98	- DELAY
	173	-	162	163	164	165	166	168	169	171	172	173	174	174	- NOISE
	258	-	244	245	247	248	249	251	253	255	257	258	260	260	- FS.LOSS
	6	-	89	57	52	46	41	30	25	22	19	17	15	15	- P. LOSS
	22	-	-64	-32	-26	-21	-16	-3	1	5	8	10	12	12	- S/N..DB
	99	-	0	0	0	1	4	35	60	77	88	93	96	96	- S/N..PROB.A
	96	-	0	0	0	0	0	7	19	30	42	51	65	65	- S/N..PROB.B
	64	-	0	0	0	0	0	0	2	5	10	15	22	22	- S/N..PROB.C
	21	-	0	0	0	0	0	0	0	0	1	1	3	3	- S/N..PROB.D
12	23.5	1F-	2F+	2F-	2F-	2F-	2F-	1F+	1F-	1F+	1F+	1F+	1F-	1F-	- MODE
	45	202	169	163	163	167	83	41	82	89	89	41	41	41	- ANGLE
	50	97	97	93	86	75	95	97	67	41	18	44	16	16	- C.PROB.
	94	103	100	100	100	100	98	93	98	98	98	93	93	93	- DELAY
	173	161	162	163	164	165	166	168	169	171	172	173	174	174	- NOISE
	257	242	243	245	247	248	249	250	253	255	257	257	260	260	- FS.LOSS
	5	83	53	47	42	37	29	11	21	18	16	5	4	4	- P. LOSS
	23	-58	-28	-22	-16	-12	-3	16	5	9	11	23	24	24	- S/N..DB
	99	0	0	1	5	12	37	99	80	90	95	99	99	99	- S/N..PROB.A
	97	0	0	0	0	1	10	82	34	46	57	97	98	98	- S/N..PROB.B
	67	0	0	0	0	0	1	36	8	14	19	68	75	75	- S/N..PROB.C
	25	0	0	0	0	0	0	9	0	2	3	25	30	30	- S/N..PROB.D
14	19.4	1F+	2F-	2F-	1F+	- MODE									
	87	146	144	72	65	63	63	67	75	86	86	86	86	- ANGLE	
	50	99	98	99	99	98	95	86	67	41	18	5	5	- C.PROB.	
	98	99	98	97	97	97	97	98	98	98	98	98	98	- DELAY	
	170	159	160	161	163	165	166	168	169	171	172	173	173	- NOISE	
	255	241	243	245	246	247	249	251	253	255	257	258	260	- FS.LOSS	
	13	41	36	26	23	21	19	16	14	13	12	11	11	- P. LOSS	
	13	-17	-12	-3	1	4	7	10	12	14	15	16	16	- S/N..DB	
	97	4	10	37	59	75	87	93	97	98	98	99	99	- S/N..PROB.A	
	70	0	1	9	18	27	41	52	66	72	78	82	82	- S/N..PROB.B	
	27	0	0	0	2	4	11	17	24	28	32	36	36	- S/N..PROB.C	
	5	0	0	0	0	0	1	2	4	6	7	9	9	- S/N..PROB.D	
16	24.0	1F-	1F+	1F-	1F-	- MODE									
	42	52	53	54	55	57	59	64	73	88	88	41	41	- ANGLE	
	50	99	99	99	99	99	99	94	78	49	20	51	16	- C.PROB.	
	93	96	96	96	96	96	97	97	97	98	98	93	93	- DELAY	
	173	158	160	162	164	165	166	168	169	171	172	173	174	- NOISE	
	258	241	243	244	246	247	249	251	253	255	257	257	260	- FS.LOSS	
	1	13	12	11	10	9	9	8	8	8	8	1	1	- P. LOSS	
	28	8	11	13	15	16	17	18	18	19	19	28	28	- S/N..DB	
	99	92	97	99	99	99	99	99	99	99	99	99	99	- S/N..PROB.A	
	99	44	60	73	84	84	87	89	90	90	91	99	99	- S/N..PROB.B	
	89	10	17	23	31	38	41	43	45	46	47	88	90	- S/N..PROB.C	
	45	0	1	3	5	10	11	13	13	14	14	43	45	- S/N..PROB.D	

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	22.3	1F-	1F+	1F-	1F-	-	-	MODE							
		51	59	60	61	63	66	68	76	89	96	48	50	-	ANGLE
		50	99	99	99	99	99	98	87	60	27	54	27	-	C.PROB.
		94	97	97	97	97	97	97	98	98	99	94	94	-	DELAY
		172	158	161	163	164	165	166	168	169	171	172	173	-	NOISE
		256	241	243	245	246	247	249	251	253	255	256	258	-	FS.LOSS
		1	11	10	9	8	8	8	8	8	1	1	-	-	P. LOSS
		27	11	14	16	16	17	18	18	19	27	28	-	-	S/N..DB
		99	98	99	99	99	99	99	99	99	99	99	-	-	S/N..PROB.A
		99	61	77	89	84	87	90	89	90	90	99	99	-	S/N..PROB.B
		86	19	26	36	39	42	45	44	45	46	85	88	-	S/N..PROB.C
		40	2	4	8	12	14	16	15	16	16	40	44	-	S/N..PROB.D
20	20.7	1F-	1F+	1F-	1F-	1F-	-	-	MODE						
		55	64	65	67	69	72	76	86	100	50	55	55	-	ANGLE
		50	99	99	99	98	95	89	69	37	59	28	7	-	C.PROB.
		94	97	97	97	97	97	98	98	99	94	94	94	-	DELAY
		171	159	162	163	164	165	166	168	169	171	172	173	-	NOISE
		255	241	243	245	246	248	249	251	254	254	256	258	-	FS.LOSS
		1	11	10	9	9	8	8	8	9	1	1	-	-	P. LOSS
		27	12	15	15	16	17	17	18	17	27	27	28	-	S/N..DB
		99	98	99	99	99	99	99	99	99	99	99	99	-	S/N..PROB.A
		99	66	83	80	84	87	87	89	87	99	99	99	-	S/N..PROB.B
		86	21	31	35	39	42	42	44	42	85	85	88	-	S/N..PROB.C
		41	3	6	10	12	14	14	15	14	39	40	44	-	S/N..PROB.D
22	19.0	1F-	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	1F-	1F-	-	-	MODE
		62	70	72	75	78	81	86	43	53	62	62	-	-	ANGLE
		50	99	99	98	95	89	79	84	63	32	7	-	-	C.PROB.
		94	97	97	98	98	98	98	94	94	94	94	-	-	DELAY
		170	161	162	163	164	165	166	168	169	171	172	-	-	NOISE
		254	241	243	245	246	248	249	250	253	254	256	-	-	FS.LOSS
		1	11	10	10	9	9	9	1	1	1	1	-	-	P. LOSS
		26	13	14	15	16	16	16	26	26	27	27	-	-	S/N..DB
		99	98	98	99	99	99	99	99	99	99	99	-	-	S/N..PROB.A
		99	70	75	80	84	84	84	99	99	99	99	-	-	S/N..PROB.B
		82	24	31	35	39	39	38	82	84	85	85	-	-	S/N..PROB.C
		37	4	8	10	12	12	12	37	38	39	40	-	-	S/N..PROB.D
24	17.4	1F-	1F+	1F+	1F+	1F+	1F-	1F-	1F-	1F-	1F-	1F-	-	-	MODE
		63	72	75	79	83	89	42	52	63	63	-	-	-	ANGLE
		50	98	96	91	84	73	85	66	37	8	-	-	-	C.PROB.
		95	97	98	98	98	98	93	94	95	95	-	-	-	DELAY
		169	161	162	163	164	165	166	168	169	171	-	-	-	NOISE
		252	241	243	245	246	248	248	251	253	255	-	-	-	FS.LOSS
		1	11	10	10	9	9	1	1	1	1	-	-	-	P. LOSS
		26	13	14	15	15	16	25	26	26	27	-	-	-	S/N..DB
		99	97	98	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A
		99	69	75	80	80	84	98	99	99	99	-	-	-	S/N..PROB.B
		82	26	30	34	34	38	80	82	84	85	-	-	-	S/N..PROB.C
		36	5	6	8	8	10	34	36	37	38	-	-	-	S/N..PROB.D

[REDACTED]

3 JUN SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C RCVR 100 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0DB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	85	64	27	10	61	48	32	10	18	99	99	70	34
4	91	56	38	15	12	99	90	55	20	20	99	98	72	36
6	71	38	9	0	14	97	72	31	5	22	99	98	87	47
8	56	24	5	0	16	99	99	68	32	24	99	98	85	44

4 JUN SSN= 110 26.015

TRANSMITTER		RECEIVER		AZIMUTHS		N.MILES									
SITE C		RCVR 150		61.0	262.8	1493.7									
SIGMA= 1000 SQ. METERS															
OFF AZIMUTH 0 DEG.		MIN. ANGLE= 4 DEG.		OFF AZIMUTH 0 DEG.		ANT= 25DB									
PWR=200.00KW		3 MC/S MAN.NOISE= -148 DBW		REQ.S/N= 0, 10, 20, 30DB											
OPERATING FREQUENCIES															
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
2	17.3	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	-	-	-	-	MODE
		108	82	79	78	79	81	84	94	107	107	-	-	-	ANGLE
		5v	99	99	97	95	91	85	66	36	8	-	-	-	C.PROB.
		100	98	98	98	98	98	99	100	100	-	-	-	-	DELAY
		169	161	162	163	164	165	166	168	169	171	-	-	-	NOISE
		253	241	243	245	246	248	249	251	254	255	-	-	-	FS.LOSS
		13	27	23	21	19	17	16	14	13	12	-	-	-	P. LOSS
		13	-2	1	4	6	8	10	12	13	15	-	-	-	S/N..DR
		97	39	59	76	84	90	94	96	97	98	-	-	-	S/N..PROB.A
		68	11	20	30	38	45	54	63	71	77	-	-	-	S/N..PROB.B
		25	1	3	7	10	14	18	23	27	31	-	-	-	S/N..PROB.C
		5	0	0	0	1	2	3	4	5	7	-	-	-	S/N..PROB.D
4	19.7	1F+	2F+	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F+	-	-	-	MODE
		102	199	152	145	144	86	81	82	88	100	100	100	100	ANGLE
		50	96	97	94	90	96	93	83	67	47	31	17	6	C.PROB.
		99	103	99	98	98	98	98	98	99	99	99	99	99	DELAY
		170	161	162	163	164	165	166	168	169	171	172	173	174	NOISE
		255	242	243	245	246	248	249	251	253	255	257	259	261	FS.LOSS
		17	75	49	43	39	28	26	22	19	17	15	14	13	P. LOSS
		9	-50	-24	-18	-13	-3	0	5	7	10	12	13	15	S/N..DR
		92	0	0	3	10	38	49	78	87	93	96	97	98	S/N..PROB.A
		49	0	0	0	1	10	16	32	41	50	62	68	80	S/N..PROB.B
		16	0	0	0	0	1	2	7	11	16	22	25	33	S/N..PROB.C
		2	0	0	0	0	0	0	1	2	4	5	8	-	S/N..PROB.D
6	20.1	1F+	-	2F+	2F+	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F+	MODE
		93	-	196	190	145	136	133	81	81	92	90	90	90	ANGLE
		50	-	92	86	91	85	77	85	70	51	34	20	7	C.PROB.
		99	-	102	102	98	98	98	98	99	99	99	99	99	DELAY
		171	-	162	163	164	165	166	168	169	171	172	173	174	NOISE
		255	-	244	245	246	248	249	251	253	255	257	258	260	FS.LOSS
		21	-	86	77	51	47	43	28	24	21	19	17	15	P. LOSS
		6	-	-61	-52	-26	-21	-16	-1	2	6	9	11	13	S/N..DR
		81	-	0	0	0	1	4	43	66	81	91	95	97	S/N..PROB.A
		34	-	0	0	0	0	0	11	22	34	46	57	70	S/N..PROB.B
		7	-	0	0	0	0	0	1	3	7	12	17	25	S/N..PROB.C
		4	-	0	0	0	0	0	0	0	1	2	4	-	S/N..PROB.D
8	19.8	1F+	-	2F+	2F+	2F+	2F-	2F-	1F+	1F+	1F+	1F+	1F+	-	MODE
		93	-	216	196	196	143	138	90	84	94	89	89	-	ANGLE
		50	-	91	84	73	83	74	84	68	48	30	16	-	C.PROB.
		99	-	103	102	102	98	98	99	98	99	98	98	-	DELAY
		170	-	162	163	164	165	166	168	169	171	172	173	-	NOISE
		255	-	244	245	246	247	248	249	251	253	255	257	258	FS.LOSS
		23	-	93	84	75	51	47	31	27	23	20	18	-	P. LOSS
		3	-	-68	-59	-50	-26	-20	-4	0	4	7	9	-	S/N..DR
		72	-	0	0	0	0	1	31	49	72	85	91	-	S/N..PROB.A
		26	-	0	0	0	0	0	6	14	26	38	47	-	S/N..PROB.B
		4	-	0	0	0	0	0	0	1	4	8	13	-	S/N..PROB.C
		0	-	0	0	0	0	0	0	0	0	0	1	-	S/N..PROB.D

		OPERATING FREQUENCIES														
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30		
1	19.3	-	2F+	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F+	-	-	MODE	
	1F+	-	210	167	158	154	156	91	93	99	99	99	-	-	ANGLE	
	101	-	90	93	87	79	69	81	63	43	25	12	-	-	C.PROB.	
	50	-	104	100	99	99	99	99	99	99	99	99	-	-	DELAY	
	99	-	162	163	164	165	166	168	169	171	172	173	-	-	NOISE	
	170	-	244	245	246	248	249	251	253	255	257	258	-	-	FSLOSS	
	255	-	88	58	53	47	43	30	25	22	19	18	-	-	P. LOSS	
	23	-	-63	-33	-27	-22	-17	-3	1	5	8	10	-	-	S/N..DB	
	3	-	0	0	0	0	3	35	60	77	88	93	-	-	S/N..PROB.A	
	70	-	0	0	0	0	0	7	19	30	42	51	-	-	S/N..PROB.B	
	25	-	0	0	0	0	0	0	2	5	10	15	-	-	S/N..PROB.C	
	4	-	0	0	0	0	0	0	0	1	1	1	-	-	S/N..PROB.D	
	0	-	0	0	0	0	0	0	0	0	1	1	-	-		
12	18.6	1F+	2F+	2F-	2F-	1F+	-	-	MODE							
	1F+	2F+	2F-	2F-	2F-	1F+	-	-	ANGLE							
	102	209	163	155	152	95	89	88	97	100	100	100	-	-	C.PROB.	
	50	97	98	95	89	97	93	80	58	30	11	-	-	DELAY		
	99	104	100	99	99	99	98	98	99	99	99	99	-	-	NOISE	
	170	161	162	163	164	165	166	168	169	171	172	-	-	FSLOSS		
	254	242	243	245	246	248	249	251	253	255	257	-	-	P. LOSS		
	28	82	53	48	43	32	29	24	21	18	16	-	-	S/N..DB		
	7	-58	-29	-23	-17	-6	-3	2	5	9	11	-	-	S/N..PROB.A		
	85	0	0	1	4	27	37	63	80	90	95	-	-	S/N..PROB.B		
	39	0	0	0	0	5	10	23	34	46	57	-	-	S/N..PROB.C		
	10	0	0	0	0	0	1	4	8	14	19	-	-	S/N..PROB.D		
	1	0	0	0	0	0	0	0	0	2	3	-	-			
14	18.6	1F+	2F-	1F+	-	-	MODE									
	1F+	2F-	1F+	-	-	ANGLE										
	98	138	85	78	74	73	74	79	91	97	97	97	-	-	C.PROB.	
	50	99	99	99	98	97	93	80	58	31	11	-	-	DELAY		
	99	98	98	98	97	97	97	98	99	99	99	99	-	-	NOISE	
	170	159	160	161	163	165	166	168	169	171	172	-	-	FSLOSS		
	254	241	243	245	246	248	249	251	253	255	257	-	-	P. LOSS		
	14	41	29	26	23	21	19	16	14	13	12	-	-	S/N..DB		
	12	-18	-6	-2	1	4	7	10	12	14	15	-	-	S/N..PROB.A		
	96	3	26	41	59	75	87	93	97	98	98	-	-	S/N..PROB.B		
	62	0	4	10	18	27	41	52	66	72	78	-	-	S/N..PROB.C		
	22	0	0	1	2	4	11	17	24	28	32	-	-	S/N..PROB.D		
	4	0	0	0	0	0	1	2	4	6	7	-	-			
16	19.1	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	-	-	MODE	
	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	-	-	ANGLE	
	99	62	63	64	66	68	70	77	87	99	99	99	-	-	C.PROB.	
	50	99	99	99	99	99	98	91	68	36	12	-	-	DELAY		
	99	97	97	97	97	97	97	98	98	99	99	99	-	-	NOISE	
	170	158	160	162	164	165	166	168	169	171	172	-	-	FSLOSS		
	255	241	243	245	246	247	249	251	253	255	257	-	-	P. LOSS		
	9	13	12	11	10	10	9	9	9	9	9	-	-	S/N..DB		
	17	8	10	13	15	16	16	17	17	18	18	-	-	S/N..PROB.A		
	99	92	96	99	99	99	99	99	99	99	99	-	-	S/N..PROB.B		
	86	44	54	73	84	84	84	86	87	88	88	-	-	S/N..PROB.C		
	40	10	14	23	31	38	37	39	41	42	43	-	-	S/N..PROB.D		
	11	0	1	3	5	10	10	11	11	12	12	-	-	S/N..PROB.D		

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	17.9	1F+	-	-	-	-	MODE								
		106	69	70	72	74	77	80	89	106	106	-	-	-	ANGLE
		50	99	99	99	99	99	96	80	48	17	-	-	-	C.PROB.
		100	97	97	97	97	98	98	98	100	100	-	-	-	DELAY
		169	158	161	163	164	165	166	168	169	171	-	-	-	NOISE
		253	241	243	245	246	248	249	251	254	255	-	-	-	FS.LOSS
		9	11	10	9	9	9	8	8	9	9	-	-	-	P. LOSS
		17	10	13	15	16	16	17	18	17	18	-	-	-	S/N..DB
		99	97	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A
		87	54	71	85	84	84	87	89	87	88	-	-	-	S/N..PROB.B
		42	16	23	32	39	39	42	44	42	43	-	-	-	S/N..PROB.C
		14	2	3	6	12	12	14	15	14	14	-	-	-	S/N..PROB.D
20	21.8	1F-	1F+	1F-	1F-	-	-	-	MODE						
		43	74	75	77	80	83	87	101	110	-	43	43	-	ANGLE
		50	99	99	99	96	92	85	61	24	-	47	18	-	C.PROB.
		94	97	98	98	98	98	98	99	100	-	94	94	-	DELAY
		172	159	162	163	164	165	166	168	169	-	172	173	-	NOISE
		256	241	243	245	246	248	249	251	254	-	256	257	-	FS.LOSS
		1	11	10	10	9	9	9	9	9	-	1	1	-	P. LOSS
		28	11	14	15	15	16	16	17	16	-	27	28	-	S/N..DB
		99	98	99	99	99	99	99	99	99	-	99	99	-	S/N..PROB.A
		99	59	78	80	80	84	84	86	84	-	99	99	-	S/N..PROB.B
		88	19	27	35	35	39	38	40	38	-	85	88	-	S/N..PROB.C
		43	2	5	10	10	12	12	13	12	-	40	44	-	S/N..PROB.D
22	20.0	1F-	1F+	1F-	1F-	-	-	-	MODE						
		50	80	82	85	89	93	99	116	116	50	50	-	-	ANGLE
		50	99	99	97	92	85	73	37	7	50	18	-	-	C.PROB.
		94	98	98	98	98	99	99	100	100	94	94	-	-	DELAY
		171	161	162	163	164	165	166	168	169	171	172	-	-	NOISE
		254	241	243	245	246	248	249	252	254	254	256	-	-	FS.LOSS
		1	11	11	10	10	9	9	10	10	1	1	-	-	P. LOSS
		27	13	14	14	15	15	16	16	16	27	27	-	-	S/N..DB
		99	98	98	98	99	99	99	99	99	99	99	-	-	S/N..PROB.A
		99	70	75	76	80	80	84	82	84	99	99	-	-	S/N..PROB.B
		85	24	31	32	35	35	38	37	38	85	85	-	-	S/N..PROB.C
		39	4	8	9	10	10	12	11	12	39	40	-	-	S/N..PROB.D
24	18.2	1F-	1F+	1F+	1F+	1F+	1F+	1F+	1F-	1F-	-	-	-	-	MODE
		52	83	86	90	95	102	114	118	49	51	-	-	-	ANGLE
		50	97	94	88	79	67	53	12	53	19	-	-	-	C.PROB.
		94	98	98	99	99	99	100	101	94	94	-	-	-	DELAY
		169	161	162	163	164	165	166	168	169	171	-	-	-	NOISE
		253	241	243	245	246	248	249	252	253	254	-	-	-	FS.LOSS
		1	11	11	10	10	10	10	10	1	1	-	-	-	P. LOSS
		26	13	13	14	15	15	15	16	26	27	-	-	-	S/N..DB
		99	97	97	98	99	99	98	99	99	99	-	-	-	S/N..PROB.A
		99	69	70	76	80	80	80	82	99	99	-	-	-	S/N..PROB.B
		84	26	26	30	34	34	34	36	84	85	-	-	-	S/N..PROB.C
		38	5	5	7	8	8	8	9	37	38	-	-	-	S/N..PROB.D

[REDACTED]

4 JUN SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C HCVR 150 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0dB(A), 10dB(B), 20dB(C), 30dB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	73	29	4	10	54	24	3	0	18	99	99	68	24
4	88	51	17	2	12	75	32	7	0	20	99	99	62	28
6	65	34	7	6	14	96	68	25	3	22	99	94	62	28
8	59	24	4	0	16	99	99	70	22	24	99	90	60	25

1 SEP SSN= 110 26.014
 TRANSMITTER RECEIVER AZIMUTHS N.MILES
 SITE C RCVR 0 61.0 262.8 1493.7
 SIGMA= 1000 SQ. METERS
 OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
 PWR=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB
 OPERATING FREQUENCIES
 GMT MUF 9 10 11 12 13 14 16 18 20 22 24 27 30

< 17.6														
1 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	MODE
72	178	41	42	44	47	50	58	71	71	-	-	-	-	ANGLE
50	95	99	99	99	97	93	74	42	13	-	-	-	-	C.PROB.
97	101	96	96	96	96	96	97	97	97	-	-	-	-	DELAY
169	161	162	163	164	165	166	168	169	171	-	-	-	-	NOISE
253	242	243	244	246	247	249	251	253	255	-	-	-	-	FS.LOSS
3	21	8	7	6	5	4	3	2	2	-	-	-	-	P. LOSS
24	2	16	18	19	20	21	23	24	25	-	-	-	-	S/N..DB
99	63	99	99	99	99	99	99	99	99	-	-	-	-	S/N..PROB.A
98	23	83	90	92	94	95	97	98	98	-	-	-	-	S/N..PROB.B
74	4	37	45	49	54	60	69	76	77	-	-	-	-	S/N..PROB.C
29	0	9	13	16	18	21	26	30	31	-	-	-	-	S/N..PROB.D
4 28.2														
1 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	-	1 F	1 F	MODE	
53	149	144	142	142	144	146	155	170	189	-	46	52	ANGLE	
50	99	99	98	97	95	91	79	60	34	-	59	32	C.PROB.	
98	99	99	98	98	99	99	99	100	102	-	96	96	DELAY	
175	161	162	163	164	165	166	168	169	171	-	174	175	NOISE	
261	241	243	245	246	248	249	251	254	256	-	260	262	FS.LOSS	
4	53	46	41	36	33	30	25	22	21	-	5	4	P. LOSS	
24	-28	-21	-16	-11	-7	-4	1	3	6	-	23	25	S/N..DB	
99	0	1	5	14	24	34	57	71	81	-	99	99	S/N..PROB.A	
98	0	0	0	2	4	8	20	27	35	-	97	98	S/N..PROB.B	
73	0	0	0	0	0	0	3	5	8	-	70	77	S/N..PROB.C	
28	0	0	0	0	0	0	0	0	1	-	27	31	S/N..PROB.D	
6 29.5														
1 F	-	2 F	2 F	2 F	2 F	2 F	1 F	2 F	2 F	-	1 F	1 F	MODE	
53	-	165	154	148	145	145	44	162	188	-	42	51	ANGLE	
50	-	99	99	98	96	93	99	67	45	-	67	45	C.PROB.	
96	-	100	99	99	99	99	96	100	102	-	96	96	DELAY	
175	-	162	163	164	165	166	168	169	171	-	174	175	NOISE	
262	-	243	245	246	248	249	251	254	256	-	260	262	FS.LOSS	
6	-	67	60	54	48	43	21	30	26	-	8	6	P. LOSS	
22	-	-42	-35	-28	-22	-17	6	-4	0	-	20	23	S/N..DB	
99	-	0	0	0	0	3	82	32	50	-	99	99	S/N..PROB.A	
97	-	0	0	0	0	0	35	6	14	-	94	97	S/N..PROB.B	
66	-	0	0	0	0	0	7	0	1	-	54	67	S/N..PROB.C	
22	-	0	0	0	0	0	0	0	0	-	16	23	S/N..PROB.D	
8 27.8														
1 F	-	-	2 F	2 F	2 F	2 F	2 F	1 F	2 F	-	1 F	1 F	MODE	
53	-	-	165	154	149	148	154	42	185	-	48	50	ANGLE	
50	-	-	99	98	95	91	77	98	23	-	56	26	C.PROB.	
96	-	-	100	99	99	99	99	96	102	-	96	96	DELAY	
175	-	-	163	164	165	166	168	169	171	-	174	175	NOISE	
261	-	-	245	246	248	249	251	253	256	-	260	262	FS.LOSS	
9	-	-	67	61	55	49	40	20	29	-	9	8	P. LOSS	
20	-	-	-42	-35	-29	-23	-13	6	-2	-	19	21	S/N..DB	
99	-	-	0	0	0	0	7	84	37	-	99	99	S/N..PROB.A	
93	-	-	0	0	0	0	0	36	8	-	92	94	S/N..PROB.B	
50	-	-	0	0	0	0	0	8	0	-	48	55	S/N..PROB.C	
14	-	-	0	0	0	0	0	0	0	-	13	17	S/N..PROB.D	

		OPERATING FREQUENCIES															
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30			
10	26.6	1 F	-	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	MODE
		67	-	180	171	169	169	172	57	47	47	49	54	65	65	65	ANGLE
		50	-	99	98	97	93	88	99	97	92	84	71	45	15	15	C.PROB.
		97	-	101	100	100	100	101	97	96	96	96	97	97	97	97	DÉLAY
		174	-	162	163	164	165	166	168	169	171	172	173	174	175	175	NOISE
		26	-	244	245	247	248	249	251	253	255	256	258	260	262	262	FSLOSS
		8	-	69	61	55	49	44	22	18	15	12	10	8	6	6	P. LOSS
		2	-	-44	-36	-29	-23	-18	5	8	13	15	17	20	22	22	S/N..DB
		99	-	0	0	0	0	2	78	90	97	98	99	99	99	99	S/N..PROB.A
		93	-	0	0	0	0	0	31	44	67	78	85	94	96	96	S/N..PROB.B
		53	-	0	0	0	0	0	6	11	23	30	38	54	61	61	S/N..PROB.C
		15	-	0	0	0	0	0	1	3	6	9	16	20	20	20	S/N..PROB.D
12	26.6	1 F	2 F	2 F	2 F	2 F	1 F	1 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	MODE
		61	163	157	155	156	51	44	175	203	203	43	48	60	60	60	ANGLE
		50	99	99	99	98	99	99	73	42	8	87	73	43	8	8	C.PROB.
		97	100	99	99	99	96	96	101	103	103	96	96	97	97	97	DÉLAY
		174	161	162	163	164	165	166	168	169	171	172	173	174	175	175	NOISE
		26	242	243	245	246	247	249	252	254	256	256	258	260	262	262	FSLOSS
		6	61	54	47	42	22	20	29	25	23	9	7	6	5	5	P. LOSS
		22	-37	-29	-22	-17	3	6	-2	0	4	19	21	22	24	24	S/N..DB
		99	0	0	1	4	71	84	39	54	72	99	99	99	99	99	S/N..PROB.A
		96	0	0	0	0	27	37	11	18	28	91	95	96	98	98	S/N..PROB.B
		64	0	0	0	0	5	10	1	3	6	47	57	65	72	72	S/N..PROB.C
		23	0	0	0	0	0	1	0	0	0	14	20	24	28	28	S/N..PROB.D
14	25.7	1 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	-	1 F	1 F	1 F	-	-	MODE
		57	141	142	144	148	151	157	173	198	-	40	47	57	-	-	ANGLE
		5	99	99	99	97	94	89	68	32	-	82	66	29	-	-	C.PROB.
		97	98	98	99	99	99	99	101	103	-	96	96	96	-	-	DÉLAY
		174	161	162	163	164	165	166	168	169	-	172	173	174	-	-	NOISE
		25	241	243	245	246	248	249	252	254	-	256	258	260	-	-	FSLOSS
		2	32	28	25	23	21	20	18	17	-	4	3	2	-	-	P. LOSS
		26	-7	-3	0	2	4	5	8	8	-	24	25	26	-	-	S/N..DB
		99	23	37	49	66	76	80	89	90	-	99	99	99	-	-	S/N..PROB.A
		99	4	9	16	24	30	34	43	45	-	98	98	99	-	-	S/N..PROB.B
		81	0	1	2	4	7	8	13	13	-	73	78	83	-	-	S/N..PROB.C
		35	0	0	0	0	0	0	1	2	-	28	32	37	-	-	S/N..PROB.D
16	21.5	1 F	2 F	2 F	2 F	2 F	2 F	2 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	MODE
		65	158	162	167	174	184	200	41	47	55	65	65	65	-	-	ANGLE
		5	99	99	95	88	76	58	97	87	69	41	14	-	-	-	C.PROB.
		97	100	100	100	101	101	103	96	96	96	97	97	-	-	-	DÉLAY
		171	161	162	163	164	165	166	168	169	171	172	173	-	-	-	NOISE
		25	242	243	245	247	248	250	251	253	255	257	258	-	-	-	FSLOSS
		1	18	16	16	15	15	15	2	2	1	1	1	-	-	-	P. LOSS
		25	6	7	8	9	9	9	24	25	26	26	27	-	-	-	S/N..DB
		99	82	87	90	92	92	92	99	99	99	99	99	-	-	-	S/N..PROB.A
		99	36	41	45	49	49	49	98	99	99	99	99	-	-	-	S/N..PROB.B
		80	9	11	13	16	16	16	74	80	81	82	85	-	-	-	S/N..PROB.C
		34	1	1	2	2	2	2	29	34	35	35	39	-	-	-	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	17.6	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	-	MODE
		75	43	44	46	48	50	53	62	75	75	-	-	-	ANGLE
		50	99	99	99	99	97	93	74	41	10	-	-	-	C.PROB.
		98	96	96	96	96	96	97	98	98	98	-	-	-	DELAY
		169	161	162	163	164	165	166	168	169	171	-	-	-	NOISE
		253	241	243	244	246	247	249	251	253	255	-	-	-	FS.LOSS
		2	6	5	4	4	3	3	2	2	1	-	-	-	P. LOSS
		25	18	19	20	21	22	23	24	25	26	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A
		98	89	92	94	96	97	97	98	99	99	-	-	-	S/N..PROB.B
		79	44	48	54	60	66	70	74	80	81	-	-	-	S/N..PROB.C
		34	15	18	21	23	26	29	31	35	36	-	-	-	S/N..PROB.D
20	15.4	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	-	MODE
		84	52	54	56	59	64	69	83	83	-	-	-	-	ANGLE
		50	99	98	96	91	83	71	37	8	-	-	-	-	C.PROB.
		98	96	96	96	97	97	97	98	98	-	-	-	-	DELAY
		167	161	162	163	164	165	166	168	169	-	-	-	-	NOISE
		251	241	243	244	246	247	249	251	253	-	-	-	-	FS.LOSS
		2	6	5	4	4	3	3	2	2	-	-	-	-	P. LOSS
		23	18	19	20	21	22	23	24	24	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	99	-	-	-	-	S/N..PROB.A
		97	89	92	94	96	97	97	98	98	-	-	-	-	S/N..PROB.B
		71	44	48	54	60	66	70	74	76	-	-	-	-	S/N..PROB.C
		29	15	18	21	23	26	29	31	32	-	-	-	-	S/N..PROB.D
22	15.0	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	-	-	MODE
		89	57	59	62	65	70	77	89	-	-	-	-	-	ANGLE
		50	99	98	95	89	80	66	29	-	-	-	-	-	C.PROB.
		98	96	97	97	97	97	98	98	-	-	-	-	-	DELAY
		167	161	162	163	164	165	166	168	-	-	-	-	-	NOISE
		251	241	243	245	246	248	249	251	-	-	-	-	-	FS.LOSS
		2	6	5	4	4	3	3	2	-	-	-	-	-	P. LOSS
		23	18	19	20	21	22	23	24	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	-	-	-	-	-	S/N..PROB.A
		97	89	92	94	96	97	97	98	-	-	-	-	-	S/N..PROB.B
		70	44	48	54	60	66	70	74	-	-	-	-	-	S/N..PROB.C
		28	15	18	21	23	26	29	31	-	-	-	-	-	S/N..PROB.D
24	14.1	1 F	1 F	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	-	-	MODE
		93	61	63	67	72	79	91	93	-	-	-	-	-	ANGLE
		50	99	98	94	85	71	52	14	-	-	-	-	-	C.PROB.
		99	97	97	97	97	98	99	99	-	-	-	-	-	DELAY
		166	161	162	163	164	165	166	168	-	-	-	-	-	NOISE
		249	241	243	245	246	248	249	251	-	-	-	-	-	FS.LOSS
		2	6	5	4	3	3	2	2	-	-	-	-	-	P. LOSS
		23	18	19	20	21	22	23	24	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	-	-	-	-	-	S/N..PROB.A
		97	89	92	94	96	97	97	98	-	-	-	-	-	S/N..PROB.B
		71	43	48	54	60	66	70	74	-	-	-	-	-	S/N..PROB.C
		27	13	15	18	21	24	27	29	-	-	-	-	-	S/N..PROB.D

~~SECRET~~

1 TRANSMITTER SITE C	SEP	SSN= 110	26.015
	RECEIVER RCVR 0	AZIMUTHS 61.0 262.8	N.MILES 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 008(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	99	84	40	10	99	89	49	12	18	99	99	90	51
4	78	64	43	16	12	99	93	52	17	20	99	99	89	45
6	95	76	41	11	14	97	91	73	32	22	99	99	88	48
8	93	70	33	7	16	99	99	90	42	24	99	99	84	41

2 SEP SSN= 110 26.615
 TRANSMITTER RECEIVER AZIMUTHS N.MILES
 SITE C RCVR 50 61.0 262.8 1493.7
 SIGMA= 1000 SQ. METERS
 OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
 Pwr=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB
 OPERATING FREQUENCIES
 GMT MUF 9 10 11 12 13 14 16 18 20 22 24 27 30

2	18.4	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	-	-	-	MODE			
	60	50	51	53	55	58	62	44	56	60	60	-	ANGLE			
	50	99	99	99	98	95	88	82	56	24	6	-	C.PROB.			
	97	96	96	96	97	97	96	96	97	97	-	-	DELAY			
	170	161	162	163	164	165	166	168	169	171	172	-	NOISE			
	253	241	243	244	246	247	249	251	253	255	257	-	FS.LOSS			
	3	13	12	11	10	9	9	3	3	2	2	-	P. LOSS			
	25	11	13	14	15	16	17	23	24	25	26	-	S/N..DB			
	99	95	97	98	99	99	99	99	99	99	99	-	S/N..PROB.A			
	98	58	70	76	80	84	87	97	98	98	99	-	S/N..PROB.B			
	77	20	26	30	34	38	41	69	76	77	82	-	S/N..PROB.C			
	31	3	5	7	8	10	11	26	30	31	35	-	S/N..PROB.D			
4	29.7	2F-	2F-	2F-	1F+	1F+	2F-	1F+	1F+	1F+	1F+	1F+	MODE			
	41	142	135	133	54	45	41	142	40	42	46	51	63	ANGLE		
	50	99	99	99	99	99	99	83	95	90	82	71	48	C.PROB.		
	96	98	98	98	96	96	96	98	96	96	96	97	97	DELAY		
	175	161	162	163	164	165	166	168	169	171	172	173	174	175		
	262	241	243	245	246	247	249	251	253	255	256	258	260	262		
	4	54	47	42	25	22	19	26	13	12	11	10	9	P. LOSS		
	24	-29	-22	-16	0	3	6	0	13	16	17	18	18	S/N..DB		
	99	0	1	5	55	71	84	52	97	99	99	99	99	S/N..PROB.A		
	98	0	0	0	18	27	37	17	71	81	85	88	90	S/N..PROB.B		
	76	0	0	0	3	5	10	2	27	35	39	43	45	S/N..PROB.C		
	31	0	0	0	0	0	1	0	5	8	10	12	13	S/N..PROB.D		
6	31.1	1F-	-	2F+	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F+	MODE		
	40	-	171	149	140	137	135	53	44	43	45	48	59	63	ANGLE	
	50	-	99	99	98	97	94	99	97	93	87	77	58	31	C.PROB.	
	96	-	100	99	98	98	98	96	96	96	96	97	97	97	DELAY	
	175	-	162	163	164	165	166	168	169	171	172	173	174	175	NOISE	
	262	-	244	245	246	248	249	251	253	255	256	258	260	262	FS.LOSS	
	6	-	76	61	55	49	44	24	20	17	15	14	12	11	P. LOSS	
	23	-	-51	-35	-29	-23	-18	2	6	10	13	14	16	18	S/N..DB	
	99	-	0	0	0	0	2	63	84	93	97	98	99	99	S/N..PROB.A	
	97	-	0	0	0	0	0	21	36	50	68	73	83	88	S/N..PROB.B	
	67	-	0	0	0	0	0	3	8	14	23	27	36	41	S/N..PROB.C	
	23	-	0	0	0	0	0	0	0	1	3	4	8	10	S/N..PROB.D	
8	26.5	1F+	-	-	2F+	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F+	MODE	
	66	-	-	-	168	148	141	138	142	50	46	48	53	63	63	ANGLE
	50	-	-	-	99	98	96	93	81	97	92	84	71	44	14	C.PROB.
	97	-	-	-	100	99	98	98	98	96	96	96	96	97	97	DELAY
	174	-	-	-	163	164	165	166	168	169	171	172	173	174	175	NOISE
	260	-	-	-	245	246	248	249	251	253	255	256	258	260	262	FS.LOSS
	14	-	-	-	77	62	56	51	41	24	20	17	15	14	12	P. LOSS
	14	-	-	-	-52	-36	-30	-24	-14	3	8	10	12	14	17	S/N..DB
	98	-	-	-	0	0	0	0	6	71	88	93	96	98	99	S/N..PROB.A
	74	-	-	-	0	0	0	0	0	25	41	51	63	75	84	S/N..PROB.B
	28	-	-	-	0	0	0	0	0	4	10	15	20	28	37	S/N..PROB.C
	5	-	-	-	0	0	0	0	0	0	1	1	3	5	8	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
10	27.9	1F-	2F+	2F-	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F-	1F-	MODE
		55	196	175	165	160	160	162	63	58	58	62	70	50	52
		50	99	99	99	97	95	90	98	95	89	78	62	57	27
		96	102	101	100	100	100	100	97	97	97	97	97	96	96
		175	161	162	163	164	165	166	168	169	171	172	173	174	175
		261	242	244	245	247	248	249	251	253	255	257	258	260	262
		8	88	70	63	56	50	45	26	22	19	17	15	8	7
		21	-64	-45	-38	-30	-24	-19	0	4	9	11	13	19	22
		99	0	0	0	0	0	2	52	76	90	95	97	99	99
		94	0	0	0	0	0	0	15	29	46	57	68	92	96
		56	0	0	0	0	0	0	1	5	12	17	24	48	61
		17	0	0	0	0	0	0	0	0	1	2	3	13	20
12	27.9	1F-	2F-	2F-	2F-	1F+	1F-	1F-	MODE						
		49	158	149	146	146	50	52	48	48	51	56	64	44	47
		50	99	99	99	99	99	99	99	97	91	80	63	59	22
		96	99	99	99	99	97	96	96	96	96	97	96	96	96
		175	161	162	163	164	165	166	168	169	171	172	173	174	175
		261	242	243	245	246	247	249	251	253	255	257	258	260	262
		5	62	55	48	43	26	24	19	16	14	13	12	6	5
		23	-37	-30	-23	-17	0	2	7	10	13	15	16	22	24
		99	0	0	1	4	49	65	86	94	97	98	99	99	99
		97	0	0	0	0	16	24	39	54	67	78	82	96	98
		67	0	0	0	0	2	4	11	18	25	32	36	65	72
		25	0	0	0	0	0	0	1	3	5	7	9	24	28
14	27.0	1F-	2F-	2F-	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F+	1F-	1F-	MODE
		45	131	132	134	137	140	145	40	44	48	54	65	44	44
		50	99	99	99	98	96	91	99	95	88	74	55	50	12
		96	98	98	98	98	99	96	96	96	96	97	96	96	96
		174	161	162	163	164	165	166	168	169	171	172	173	174	175
		261	241	243	245	246	248	249	251	253	255	256	258	260	262
		2	32	28	25	23	21	20	10	9	8	8	8	2	2
		26	-7	-3	0	2	4	5	17	18	20	20	20	26	27
		99	23	37	49	66	76	80	99	99	99	99	99	99	99
		99	4	9	16	24	30	34	86	90	93	93	93	99	99
		83	0	1	2	4	7	8	39	45	50	51	51	83	84
		37	0	0	0	0	0	0	11	13	16	17	17	37	38
16	22.5	1F-	1F+	1F-	1F-	-	MODE								
		54	42	43	44	45	47	48	53	60	72	50	54	-	ANGLE
		50	99	99	99	99	99	99	94	81	57	57	28	-	C.PROB.
		96	96	96	96	96	96	96	96	97	97	96	96	-	DELAY
		172	161	162	163	164	165	166	168	169	171	172	173	-	NOISE
		257	241	243	244	246	247	249	251	253	255	256	258	-	FSLOSS
		1	10	9	8	7	7	7	6	6	7	1	1	-	P. LOSS
		26	15	16	17	18	18	19	20	20	20	26	27	-	S/N..DB
		99	98	99	99	99	99	99	99	99	99	99	99	-	S/N..PROB.A
		99	78	83	87	90	90	92	93	94	93	99	99	-	S/N..PROB.B
		83	32	37	41	45	45	49	52	54	50	82	85	-	S/N..PROB.C
		36	7	9	11	14	14	16	17	18	16	35	39	-	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	18.4	1F-	1F+	1F+	1F+	1F+	1F-	1F-	1F-	1F-	-	-	-	-	MODE
		64	53	54	56	59	62	41	48	60	64	-	-	-	ANGLE
		50	99	99	99	98	95	96	83	56	22	-	-	-	C.PROB.
		97	96	96	96	97	97	96	96	97	97	-	-	-	DELAY
		170	161	162	163	164	165	166	168	169	171	-	-	-	NOISE
		254	241	243	244	246	247	249	251	253	255	-	-	-	FS.LOSS
		2	10	9	9	8	8	3	2	2	1	-	-	-	P. LOSS
		25	14	15	16	17	17	23	24	25	26	-	-	-	S/N..DB
		99	98	98	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A
		98	74	79	84	87	87	97	98	99	99	-	-	-	S/N..PROB.B
		77	31	35	38	42	42	70	74	80	81	-	-	-	S/N..PROB.C
		33	8	10	12	14	14	29	31	35	36	-	-	-	S/N..PROB.D
20	16.1	1F-	-	-	-	-	-	MODE							
		72	41	43	45	48	51	55	71	72	-	-	-	-	ANGLE
		50	99	99	97	94	88	79	52	16	-	-	-	-	C.PROB.
		97	96	96	96	96	96	96	97	97	-	-	-	-	DELAY
		168	161	162	163	164	165	166	168	169	-	-	-	-	NOISE
		251	241	243	244	246	247	249	251	253	-	-	-	-	FS.LOSS
		2	7	5	5	4	3	3	2	2	-	-	-	-	P. LOSS
		24	18	19	20	21	22	23	24	25	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	99	-	-	-	-	S/N..PROB.A
		98	89	92	94	96	97	97	98	99	-	-	-	-	S/N..PROB.B
		74	44	48	54	60	66	70	74	80	-	-	-	-	S/N..PROB.C
		31	15	18	21	23	26	29	31	35	-	-	-	-	S/N..PROB.D
22	15.7	1F-	-	-	-	-	-	MODE							
		78	46	48	50	54	57	62	78	78	-	-	-	-	ANGLE
		50	99	99	97	93	85	75	44	11	-	-	-	-	C.PROB.
		98	96	96	96	96	97	97	98	98	-	-	-	-	DELAY
		168	161	162	163	164	165	166	168	169	-	-	-	-	NOISE
		251	241	243	244	246	247	249	251	253	-	-	-	-	FS.LOSS
		2	6	5	4	4	3	3	2	2	-	-	-	-	P. LOSS
		24	18	19	20	21	22	23	24	25	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	99	-	-	-	-	S/N..PROB.A
		98	89	92	94	96	97	97	98	99	-	-	-	-	S/N..PROB.B
		72	44	48	54	60	66	70	74	80	-	-	-	-	S/N..PROB.C
		30	15	18	21	23	26	29	31	35	-	-	-	-	S/N..PROB.D
24	14.7	1F-	-	-	-	-	-	MODE							
		82	50	52	56	60	65	73	82	-	-	-	-	-	ANGLE
		50	99	99	96	90	79	63	24	-	-	-	-	-	C.PROB.
		98	96	96	96	97	97	97	98	-	-	-	-	-	DELAY
		167	161	162	163	164	165	166	168	-	-	-	-	-	NOISE
		250	241	243	244	246	247	249	251	-	-	-	-	-	FS.LOSS
		2	6	5	4	4	3	3	2	-	-	-	-	-	P. LOSS
		24	18	19	20	21	22	23	24	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	99	-	-	-	-	-	S/N..PROB.A
		98	89	92	94	96	97	97	98	-	-	-	-	-	S/N..PROB.B
		73	43	48	54	60	66	70	74	-	-	-	-	-	S/N..PROB.C
		29	13	15	18	21	24	27	29	-	-	-	-	-	S/N..PROB.D

2 SEP SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C HCVR 50 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0dB(A), 10dB(B), 20dB(C), 30dB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	99	79	34	10	97	74	39	9	18	99	99	90	50
4	99	95	58	20	12	99	93	55	20	20	99	99	89	49
6	99	87	41	11	14	99	98	81	30	22	99	99	96	51
8	95	71	26	3	16	99	99	86	33	24	99	99	88	44

3 SEP SSN= 110 26.015
 TRANSMITTER RECEIVER AZIMUTHS N.MILES
 SITE C HCVR 100 61.0 262.8 1493.7
 SIGMA= 1000 SQ. METERS
 OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
 PWR=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB
 OPERATING FREQUENCIES
 GMT MUF 9 10 11 12 13 14 16 18 20 22 24 27 30
 2 19.4
 1F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F- 1F- - - - MODE
 48 60 62 64 67 70 75 92 93 48 48 - - - ANGLE
 50 99 99 99 97 92 82 52 17 40 14 - - - C.PROB.
 94 97 97 97 97 97 98 99 99 94 94 - - - DELAY
 170 161 162 163 164 165 166 168 169 171 172 - - - NOISE
 254 241 243 245 246 248 249 251 253 254 256 - - - FS.LOSS
 1 14 12 11 10 10 10 9 1 1 - - - P. LOSS
 26 11 12 13 14 15 16 16 17 27 27 - - - S/N..DB
 99 95 96 97 98 99 99 99 99 99 99 - - - S/N..PROB.A
 99 58 65 71 76 80 84 82 87 99 99 - - - S/N..PROB.B
 83 20 23 27 31 34 37 36 41 85 85 - - - S/N..PROB.C
 37 3 4 5 7 8 10 9 11 38 39 - - - S/N..PROB.D
 4 25.6
 1F+ 2F- 2F- 1F+ MODE
 76 136 128 124 60 54 51 50 51 54 59 66 75 75 ANGLE
 50 99 99 99 99 99 99 97 94 87 76 63 34 10 C.PROB.
 98 98 97 97 97 96 96 96 96 97 97 97 98 98 DELAY
 174 161 162 163 164 165 166 168 169 171 172 173 174 175 NOISE
 259 241 243 245 246 247 249 251 253 255 257 258 260 262 FS.LOSS
 18 44 38 34 24 22 20 16 14 12 11 11 11 9 P. LOSS
 18 -18 -13 -9 0 3 6 10 13 15 16 17 18 20 S/N..DB
 99 3 9 18 55 71 84 93 97 98 99 99 99 99 S/N..PROB.A
 88 0 1 3 18 27 37 52 71 77 82 85 90 93 S/N..PROB.B
 42 0 0 0 3 5 10 17 27 31 35 39 45 50 S/N..PROB.C
 12 0 0 0 0 0 1 2 5 7 9 10 13 16 S/N..PROB.D
 6 26.9
 1F+ - 2F+ 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ MODE
 77 - 175 145 134 128 126 60 54 54 57 62 75 75 ANGLE
 50 - 99 99 99 97 96 98 95 91 82 71 49 19 C.PROB.
 98 - 101 98 98 97 97 97 96 96 97 97 98 98 DELAY
 174 - 162 163 164 165 166 168 169 171 172 173 174 175 NOISE
 269 - 244 245 246 248 249 251 253 255 257 258 260 262 FS.LOSS
 13 - 75 48 44 40 36 24 20 18 15 14 13 11 P. LOSS
 15 - -51 -23 -18 -14 -10 2 6 10 12 14 15 17 S/N..DB
 98 - 0 0 2 6 14 63 84 93 96 98 98 99 S/N..PROB.A
 79 - 0 0 0 0 1 21 36 50 62 73 80 84 S/N..PROB.B
 32 - 0 0 0 0 0 3 8 14 20 27 32 37 S/N..PROB.C
 6 - 0 0 0 0 0 0 0 1 3 4 6 8 S/N..PROB.D
 8 25.3
 1F+ - - 2F+ 2F- 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ MODE
 78 - - 174 143 134 129 129 59 58 61 69 75 75 ANGLE
 50 - - 98 99 97 95 85 95 89 78 62 29 7 C.PROB.
 98 - - 101 98 98 98 97 97 97 97 97 98 98 DELAY
 173 - - 163 164 165 166 168 169 171 172 173 174 175 NOISE
 259 - - 245 246 248 249 251 253 255 257 258 260 262 FS.LOSS
 15 - - 76 49 45 41 34 23 20 18 16 14 12 P. LOSS
 12 - - -51 -24 -19 -15 -7 3 7 10 12 14 16 S/N..DB
 97 - - 0 0 2 5 21 71 85 93 96 98 99 S/N..PROB.A
 66 - - 0 0 0 0 3 25 37 51 63 75 81 S/N..PROB.B
 22 - - 0 0 0 0 0 0 4 8 15 20 28 33 S/N..PROB.C
 3 - - 0 0 0 0 0 0 0 0 1 3 5 7 S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
10	29.4	1F+	2F-	2F-	2F-	2F-	2F-	1F+	- MODE						
		42	203	169	158	152	150	151	71	68	70	76	87	88	- ANGLE
		50	99	99	99	98	96	92	98	93	85	71	53	19	- C.PROB.
		93	103	100	99	99	99	99	97	97	97	98	98	98	- DELAY
		175	161	162	163	164	165	166	168	169	171	172	173	174	- NOISE
		261	242	243	245	246	248	249	251	253	255	257	258	260	- FSLOSS
		4	87	56	50	45	41	37	26	22	19	17	15	14	- P. LOSS
		25	-63	-31	-25	-20	-15	-11	0	4	8	11	12	14	- S/N..DB
		99	0	0	0	1	5	11	52	76	88	95	96	98	- S/N..PROB.A
		98	0	0	0	0	0	1	15	29	41	57	63	75	- S/N..PROB.B
		80	0	0	0	0	0	0	1	5	10	17	20	28	- S/N..PROB.C
		32	0	0	0	0	0	0	0	0	1	2	3	5	- S/N..PROB.D
12	24.3	1F+	2F-	2F-	2F-	1F+	- MODE								
		84	153	143	138	136	66	61	58	60	64	70	82	83	- ANGLE
		50	99	99	99	99	99	99	95	87	72	53	11	- C.PROB.	
		98	99	98	98	98	97	97	97	97	97	98	98	98	- DELAY
		173	161	162	163	164	165	166	168	169	171	172	173	174	- NOISE
		269	241	243	245	246	247	249	251	253	255	257	258	260	- FSLOSS
		12	50	44	39	35	26	23	19	17	15	13	12	11	- P. LOSS
		15	-25	-19	-14	-10	0	2	7	10	13	14	15	16	- S/N..DB
		98	0	3	8	16	49	65	86	94	97	98	98	99	- S/N..PROB.A
		78	0	0	0	2	16	24	39	54	67	73	78	83	- S/N..PROB.B
		32	0	0	0	0	2	4	11	18	25	28	32	37	- S/N..PROB.C
		7	0	0	0	0	0	1	3	5	6	7	9	- S/N..PROB.D	
14	23.4	1F+	- MODE												
		80	49	47	47	47	48	49	51	55	61	70	80	-	- ANGLE
		50	99	99	99	99	99	99	98	93	82	65	39	-	- C.PROB.
		98	96	96	96	96	96	96	96	96	97	97	98	-	- DELAY
		172	161	162	163	164	165	166	168	169	171	172	173	-	- NOISE
		268	241	243	244	246	247	249	251	253	255	257	258	-	- FSLOSS
		9	21	18	16	14	13	12	10	9	9	9	9	-	- P. LOSS
		18	3	6	9	11	12	14	16	17	19	19	19	-	- S/N..DB
		99	69	83	92	96	97	98	99	99	99	99	99	-	- S/N..PROB.A
		98	26	37	49	60	66	75	82	87	90	91	91	-	- S/N..PROB.B
		46	5	9	16	21	24	30	36	41	46	47	47	-	- S/N..PROB.C
		14	0	1	2	3	4	7	9	11	14	14	15	-	- S/N..PROB.D
16	23.8	1F+	1F-	1F-	1F-	- MODE									
		42	52	53	54	56	57	59	65	74	87	87	42	42	- ANGLE
		50	99	99	99	99	99	98	91	72	43	14	46	11	- C.PROB.
		98	96	96	96	96	97	97	97	97	98	98	93	93	- DELAY
		173	161	162	163	164	165	166	168	169	171	172	173	174	- NOISE
		267	241	243	244	246	247	249	251	253	255	257	257	260	- FSLOSS
		1	10	9	9	8	8	7	7	7	8	8	1	0	- P. LOSS
		28	14	15	16	17	18	18	19	19	19	20	28	28	- S/N..DB
		99	98	98	99	99	99	99	99	99	99	99	99	99	- S/N..PROB.A
		99	74	79	84	87	90	90	91	92	90	93	99	99	- S/N..PROB.B
		88	29	33	37	41	45	45	47	49	46	51	88	90	- S/N..PROB.C
		42	6	8	10	12	14	13	15	16	14	17	43	45	- S/N..PROB.D

		OPERATING FREQUENCIES																
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30				
18	19.4	1F-	1F+	1F-	1F-	1F-	-	-	-	MODE								
		53	63	65	67	70	73	78	94	43	52	52	-	-	-	ANGLE		
		50	99	99	99	97	92	83	53	69	38	11	-	-	-	C.PROB.		
		94	97	97	97	97	97	98	99	94	94	94	-	-	-	DELAY		
		170	161	162	163	164	165	166	168	169	171	172	-	-	-	NOISE		
		254	241	243	245	246	248	249	251	252	254	256	-	-	-	FS.LOSS		
		1	11	10	9	9	9	8	9	1	1	1	-	-	-	P. LOSS		
		26	14	15	15	16	17	17	17	26	27	27	-	-	-	S/N..DB		
		99	98	98	99	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A		
		99	74	79	80	84	87	87	86	99	99	99	-	-	-	S/N..PROB.B		
		83	31	35	35	39	42	42	40	84	85	85	-	-	-	S/N..PROB.C		
		38	8	10	10	12	14	14	13	38	39	40	-	-	-	S/N..PROB.D		
20	16.9	1F-	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	1F-	1F-	-	-	-	MODE		
		61	72	75	79	83	90	42	53	61	61	-	-	-	ANGLE			
		50	99	96	92	83	70	85	63	29	6	-	-	-	C.PROB.			
		94	97	98	98	98	99	93	94	94	94	-	-	-	DELAY			
		169	161	162	163	164	165	166	168	169	171	-	-	-	NOISE			
		252	241	243	245	246	248	248	251	253	254	-	-	-	FS.LOSS			
		1	11	10	10	9	9	1	1	1	1	-	-	-	P. LOSS			
		26	13	14	15	15	16	25	26	26	27	-	-	-	S/N..DB			
		99	97	98	99	99	99	99	99	99	99	-	-	-	S/N..PROB.A			
		99	69	75	80	80	84	98	99	99	99	-	-	-	S/N..PROB.B			
		81	28	31	35	35	39	80	82	84	85	-	-	-	S/N..PROB.C			
		36	7	8	10	10	12	35	37	38	39	-	-	-	S/N..PROB.D			
22	16.4	1F-	1F+	1F+	1F+	1F-	1F-	1F-	1F-	-	-	-	-	-	MODE			
		67	77	80	84	42	45	49	62	67	-	-	-	-	ANGLE			
		50	98	96	90	95	90	82	56	21	-	-	-	-	C.PROB.			
		95	98	98	98	93	94	94	94	95	-	-	-	-	DELAY			
		168	161	162	163	164	165	166	168	169	-	-	-	-	NOISE			
		251	241	243	245	245	247	248	251	253	-	-	-	-	FS.LOSS			
		1	11	11	10	2	2	1	1	1	-	-	-	-	P. LOSS			
		25	13	14	14	23	24	25	26	26	-	-	-	-	S/N..DB			
		99	97	98	98	99	99	99	99	99	-	-	-	-	S/N..PROB.A			
		98	69	75	76	97	98	98	99	99	-	-	-	-	S/N..PROB.B			
		79	28	31	32	71	76	80	82	84	-	-	-	-	S/N..PROB.C			
		35	7	8	9	29	32	35	37	38	-	-	-	-	S/N..PROB.D			
24	15.3	1F-	1F+	1F-	1F-	1F-	1F-	1F-	1F-	-	-	-	-	-	MODE			
		71	82	41	44	47	52	57	70	70	-	-	-	-	ANGLE			
		50	99	99	98	94	86	73	37	8	-	-	-	-	C.PROB.			
		95	98	93	94	94	94	94	95	95	-	-	-	-	DELAY			
		167	161	162	163	164	165	166	168	169	-	-	-	-	NOISE			
		250	241	242	244	245	247	248	251	253	-	-	-	-	FS.LOSS			
		1	11	3	2	2	2	1	1	1	-	-	-	-	P. LOSS			
		25	13	22	23	23	24	25	26	26	-	-	-	-	S/N..DB			
		99	97	99	99	99	99	99	99	99	-	-	-	-	S/N..PROB.A			
		99	69	96	97	97	98	98	99	99	-	-	-	-	S/N..PROB.B			
		80	26	65	71	71	76	80	82	84	-	-	-	-	S/N..PROB.C			
		34	5	23	27	27	30	34	36	37	-	-	-	-	S/N..PROB.D			

[REDACTED]

3 SEP SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C HCVR 100 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0DB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	98	55	22	10	95	64	40	16	18	99	99	78	40
4	99	93	55	16	12	99	86	43	9	20	99	98	85	44
6	99	82	35	5	14	99	99	70	24	22	99	99	93	49
8	93	65	21	2	16	99	99	81	32	24	99	99	93	49

4 SEP SSN= 110 26.015

TRANSMITTER SITE C	RECEIVER RCVR 150	AZIMUTHS 61.0 262.8	N.MILES 1493.7
SIGMA= 1000 SQ. METERS			ANT= 25DB
OFF AZIMUTH 0 DEG.	MIN. ANGLE= 4 DEG.	OFF AZIMUTH 0 DEG.	
PWR=200.00KW	3 MC/S MAN.NOISE= -148 DBW	REQ.S/N= 0, 10, 20, 30DB	
OPERATING FREQUENCIES			
GMT	MUF	9 10 11 12 13 14 16 18 20 22 24 27 30	
2	15.5	1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ - - - -	MODE
		104 70 72 75 78 82 88 104 104 - - - -	ANGLE
		50 99 99 98 95 87 75 40 10 - - - -	C.PROB.
		100 97 97 98 98 98 100 100 - - - -	DELAY
		167 161 162 163 164 165 166 168 169 - - - -	NOISE
		251 241 243 245 246 248 249 252 254 - - - -	FS.LOSS
		10 14 13 12 11 10 10 10 10 - - - -	P. LOSS
		15 10 12 13 14 15 15 16 16 - - - -	S/N..DB
		99 93 96 97 98 99 98 99 99 - - - -	S/N..PROB.A
		81 52 65 71 76 80 80 82 84 - - - -	S/N..PROB.B
		34 17 23 27 31 34 34 36 37 - - - -	S/N..PROB.C
		8 2 4 5 7 8 8 9 10 - - - -	S/N..PROB.D
4	24.5	1F+ 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ -	MODE
		87 131 121 75 67 62 61 60 62 66 72 83 86 -	ANGLE
		50 99 99 99 99 99 96 91 83 70 54 22 -	C.PROB.
		98 97 98 97 97 97 97 97 97 97 98 98 -	DELAY
		173 161 162 163 164 165 166 168 169 171 172 173 174 -	NOISE
		259 241 243 245 246 247 249 251 253 255 257 258 260 -	FS.LOSS
		11 44 39 27 24 22 20 16 14 13 12 11 10 -	P. LOSS
		16 -19 -14 -2 0 3 6 10 12 15 16 16 17 -	S/N..DB
		99 2 8 41 55 71 84 93 97 98 99 99 99 -	S/N..PROB.A
		83 0 0 11 18 27 37 52 66 77 82 82 87 -	S/N..PROB.B
		36 0 0 1 3 5 10 17 24 31 35 36 41 -	S/N..PROB.C
		9 0 0 0 0 0 1 2 4 7 9 9 11 -	S/N..PROB.D
6	25.7	1F+ 2F+ 2F+ 2F+ 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ -	MODE
		89 192 181 175 128 121 117 67 64 66 70 77 87 87 -	ANGLE
		50 99 99 98 99 98 97 97 94 87 77 64 36 11 -	C.PROB.
		98 102 101 101 97 97 97 97 97 97 98 98 98 98 -	DELAY
		174 161 162 163 164 165 166 168 169 171 172 173 174 175 -	NOISE
		26 242 244 245 246 247 249 251 253 255 257 258 260 262 -	FS.LOSS
		14 83 75 67 45 41 37 24 20 18 16 14 13 12 -	P. LOSS
		14 -59 -50 -42 -19 -15 -10 2 6 10 12 13 14 17 -	S/N..DB
		98 0 0 0 2 5 14 63 84 93 96 97 98 99 -	S/N..PROB.A
		72 0 0 0 0 0 1 21 36 50 62 68 75 84 -	S/N..PROB.B
		26 0 0 0 0 0 0 3 8 14 20 24 28 37 -	S/N..PROB.C
		4 0 0 0 0 0 0 0 0 1 3 3 5 8 -	S/N..PROB.D
8	24.2	1F+ - 2F+ 2F+ 2F+ 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F+ 1F+ -	MODE
		89 - 191 180 176 128 121 76 69 70 75 87 87 -	ANGLE
		50 - 99 98 95 98 96 98 93 85 70 52 18 -	C.PROB.
		98 - 102 101 101 97 97 98 97 97 98 98 98 -	DELAY
		173 - 162 163 164 165 166 168 169 171 172 173 174 -	NOISE
		259 - 244 245 247 248 249 251 253 255 257 258 260 -	FS.LOSS
		16 - 83 75 68 46 42 27 23 20 18 16 14 -	P. LOSS
		11 - -59 -51 -43 -20 -15 -0 3 7 10 11 13 -	S/N..DB
		95 - 0 0 0 1 5 47 71 85 93 95 97 -	S/N..PROB.A
		58 - 0 0 0 0 0 13 25 37 51 57 70 -	S/N..PROB.B
		18 - 0 0 0 0 0 0 1 4 8 15 17 25 -	S/N..PROB.C
		2 - 0 0 0 0 0 0 0 0 1 2 4 -	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30
10	23.3	1F+	2F+	2F-	2F-	2F-	1F+	-						
		101	207	198	153	145	141	89	79	78	82	90	99	99
		50	99	99	99	98	97	99	97	91	80	63	41	10
		99	103	103	99	98	98	98	98	98	99	99	99	-
		172	161	162	163	164	165	166	168	169	171	172	173	174
		258	242	244	245	246	248	249	251	253	255	257	259	261
		16	86	77	51	46	42	31	26	22	19	17	16	14
		14	-62	-53	-26	-21	-16	-4	0	4	8	10	12	13
		94	0	0	0	1	4	32	52	76	88	93	96	97
		55	0	0	0	0	0	6	15	29	41	51	63	70
		17	0	0	0	0	0	0	1	5	10	15	20	25
		2	0	0	0	0	0	0	0	0	1	1	3	4
12	23.3	1F+	2F-	2F-	2F-	1F+	-							
		95	150	136	129	81	73	70	69	71	76	85	94	-
		50	99	99	99	99	99	99	98	93	82	64	37	-
		99	99	98	98	98	97	97	97	97	98	98	99	-
		172	161	162	163	164	165	166	168	169	171	172	173	-
		258	241	243	245	246	248	249	251	253	255	257	258	-
		13	50	45	40	29	26	23	19	17	15	14	13	-
		13	-25	-20	-15	-3	0	2	7	9	12	14	15	-
		98	0	2	7	38	49	65	86	92	96	98	98	-
		71	0	0	0	10	16	24	39	49	62	73	78	-
		27	0	0	0	1	2	4	11	16	22	28	32	-
		6	0	0	0	0	0	0	1	2	4	6	7	-
14	22.4	1F+	-											
		91	58	57	57	57	58	59	63	67	74	87	91	-
		50	99	99	99	99	99	99	97	90	75	55	22	-
		99	97	97	96	97	97	97	97	97	98	98	99	-
		172	161	162	163	164	165	166	168	169	171	172	173	-
		257	241	243	244	246	247	249	251	253	255	257	258	-
		14	21	18	16	15	13	12	11	10	9	9	9	-
		18	3	6	8	10	12	13	16	16	18	18	18	-
		99	69	83	90	94	97	97	99	99	99	99	99	-
		89	26	37	45	55	66	70	82	84	88	88	88	-
		44	5	9	13	18	24	27	36	37	42	43	43	-
		13	0	1	2	3	4	5	9	10	12	12	12	-
10	18.9	1F+	-											
		98	62	63	64	66	68	71	77	89	98	98	98	-
		5	99	99	99	99	99	97	86	63	29	6	-	-
		99	97	97	97	97	97	97	98	98	99	99	99	-
		17	161	162	163	164	165	166	168	169	171	172	172	-
		254	241	243	245	246	247	249	251	253	255	257	257	-
		9	11	10	9	9	8	8	8	8	8	8	8	-
		18	14	15	16	16	17	17	18	18	19	19	19	-
		99	98	98	99	99	99	99	99	99	99	99	99	-
		89	74	79	84	84	87	87	89	90	90	91	91	-
		43	29	33	37	38	41	41	43	45	46	47	47	-
		13	6	8	10	10	12	11	13	13	14	14	14	-

		OPERATING FREQUENCIES														
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30		
18	20.4	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	-	1F-	1F-	-	-	-	MODE
		40	73	75	78	81	85	91	107	107	-	40	40	-	-	ANGLE
		50	99	99	98	95	88	76	40	7	-	24	5	-	-	C.PROB.
		93	97	98	98	98	98	99	100	100	-	93	93	-	-	DELAY
		171	161	162	163	164	165	166	168	169	-	172	173	-	-	NOISE
		255	241	243	245	246	248	249	252	254	-	256	257	-	-	FS.LOSS
		1	11	10	10	9	9	9	9	9	-	1	1	-	-	P. LOSS
		27	13	14	15	15	16	16	16	17	-	28	28	-	-	S/N..DB
		99	97	98	99	99	99	99	99	99	-	99	99	-	-	S/N..PROB.A
		99	69	75	80	80	84	84	82	87	-	99	99	-	-	S/N..PROB.B
		86	28	31	35	35	39	38	37	42	-	88	88	-	-	S/N..PROB.C
		40	7	8	10	10	12	12	11	14	-	43	44	-	-	S/N..PROB.D
20	17.8	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F-	-	-	-	-	-	MODE
		49	83	86	90	95	104	115	115	49	49	-	-	-	-	ANGLE
		50	98	95	89	78	62	43	8	45	14	-	-	-	-	C.PROB.
		94	98	98	99	99	99	100	100	94	94	-	-	-	-	DELAY
		169	161	162	163	164	165	166	168	169	171	-	-	-	-	NOISE
		252	241	243	245	246	248	249	252	253	254	-	-	-	-	FS.LOSS
		1	11	11	10	10	10	10	10	1	1	-	-	-	-	P. LOSS
		26	13	13	14	14	15	15	16	26	27	-	-	-	-	S/N..DB
		99	97	97	98	98	99	98	99	99	99	-	-	-	-	S/N..PROB.A
		99	69	70	76	76	80	80	82	99	99	-	-	-	-	S/N..PROB.B
		83	28	28	32	32	35	35	37	84	85	-	-	-	-	S/N..PROB.C
		38	7	7	9	9	10	10	11	38	39	-	-	-	-	S/N..PROB.D
22	17.3	1F+	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	-	-	-	-	-	MODE
		55	88	91	96	102	112	120	45	55	55	-	-	-	-	ANGLE
		50	98	94	87	74	58	36	67	36	9	-	-	-	-	C.PROB.
		94	98	99	99	99	100	101	94	94	94	-	-	-	-	DELAY
		169	161	162	163	164	165	166	168	169	171	-	-	-	-	NOISE
		252	241	243	245	246	248	249	250	253	254	-	-	-	-	FS.LOSS
		1	12	11	10	10	10	10	1	1	1	-	-	-	-	P. LOSS
		26	12	13	14	14	14	14	26	26	27	-	-	-	-	S/N..DB
		99	96	97	98	98	98	98	99	99	99	-	-	-	-	S/N..PROB.A
		99	63	70	76	76	76	75	99	99	99	-	-	-	-	S/N..PROB.B
		82	25	28	32	32	32	32	82	84	85	-	-	-	-	S/N..PROB.C
		37	6	7	9	9	9	9	37	38	39	-	-	-	-	S/N..PROB.D
24	16.1	1F+	1F+	1F+	1F+	1F+	1F-	1F-	1F-	-	-	-	-	-	-	MODE
		59	92	97	103	113	124	43	58	59	-	-	-	-	-	ANGLE
		50	98	93	82	64	40	82	52	17	-	-	-	-	-	C.PROB.
		94	99	99	99	100	101	94	94	94	-	-	-	-	-	DELAY
		168	161	162	163	164	165	166	168	169	-	-	-	-	-	NOISE
		251	241	243	245	247	248	248	251	253	-	-	-	-	-	FS.LOSS
		1	12	11	11	11	11	1	1	1	-	-	-	-	-	P. LOSS
		26	12	13	13	14	14	25	26	26	-	-	-	-	-	S/N..DB
		99	96	97	97	98	98	99	99	99	-	-	-	-	-	S/N..PROB.A
		99	63	70	71	76	76	98	99	99	-	-	-	-	-	S/N..PROB.B
		82	23	26	27	31	30	80	82	84	-	-	-	-	-	S/N..PROB.C
		36	4	5	5	7	7	34	36	37	-	-	-	-	-	S/N..PROB.D

[REDACTED]

4 SEP SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N,MILES
SITE C RCVR 150 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0DB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	99	97	57	15	10	91	59	16	1	18	99	99	70	28
4	99	91	51	13	12	99	79	36	6	20	99	90	56	24
6	98	76	33	3	14	99	99	67	21	22	99	90	71	34
8	93	59	18	1	16	99	99	77	29	24	99	96	79	37

1 DEG SSN= 110 26.015
 TRANSMITTER RECEIVER AZIMUTHS N.MILES
 SITE C RCVR 0 61.0 262.8 1493.7
 SIGMA= 1000 SQ. METERS
 OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
 PWR=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB
 OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30		
2	10.4	1 F	1 F	1 F	1 F	-	-	-	-	-	-	-	-	-	MODE	
		75	58	68	75	75	-	-	-	-	-	-	-	-	ANGLE	
		50	82	61	31	8	-	-	-	-	-	-	-	-	C.PROB.	
		98	97	97	98	98	-	-	-	-	-	-	-	-	DELAY	
		163	161	162	163	164	-	-	-	-	-	-	-	-	NOISE	
		244	241	243	245	246	-	-	-	-	-	-	-	-	FS.LOSS	
		4	6	5	4	3	-	-	-	-	-	-	-	-	P. LOSS	
		21	18	20	21	21	-	-	-	-	-	-	-	-	S/N..DB	
		99	99	99	99	99	-	-	-	-	-	-	-	-	S/N..PROB.A	
		95	89	94	95	96	-	-	-	-	-	-	-	-	S/N..PROB.B	
		56	43	53	60	60	-	-	-	-	-	-	-	-	S/N..PROB.C	
		19	13	18	21	21	-	-	-	-	-	-	-	-	S/N..PROB.D	
4	21.2	1 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	-	1 F	1 F	1 F	-	MODE	
		55	145	148	152	158	167	182	193	-	46	54	54	-	ANGLE	
		50	99	99	99	95	83	60	13	-	72	36	10	-	C.PROB.	
		96	99	99	99	100	100	101	102	-	96	96	96	-	DELAY	
		171	161	162	163	164	165	166	168	-	171	172	173	-	NOISE	
		256	241	243	245	247	248	250	252	-	255	256	258	-	FS.LOSS	
		2	24	21	20	18	17	17	16	-	3	2	2	-	P. LOSS	
		25	0	3	5	6	7	8	9	-	25	25	26	-	S/N..DB	
		99	52	70	80	84	87	90	91	-	99	99	99	-	S/N..PROB.A	
		99	17	26	34	38	41	45	47	-	98	98	99	-	S/N..PROB.B	
		8	2	5	8	10	12	13	15	-	77	78	82	-	S/N..PROB.C	
		34	0	0	0	1	1	1	2	-	31	32	36	-	S/N..PROB.D	
5	32.2	1 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	2 F	-	MODE	
		47	143	137	134	133	133	134	138	145	155	181	179	-	ANGLE	
		50	99	99	99	99	99	99	96	80	47	17	-	-	C.PROB.	
		96	99	98	98	98	98	98	99	99	101	101	-	-	DELAY	
		173	161	162	163	164	165	166	168	169	171	172	173	-	NOISE	
		263	241	243	245	246	248	249	251	253	255	257	259	-	FS.LOSS	
		3	47	41	36	33	30	27	23	20	19	18	17	-	P. LOSS	
		23	-22	-16	-11	-7	-4	-1	3	5	8	9	10	-	S/N..DB	
		99	0	4	11	22	33	44	69	80	88	91	93	-	S/N..PROB.A	
		97	0	0	1	3	6	11	24	32	41	46	51	-	S/N..PROB.B	
		68	0	0	0	0	1	4	6	10	12	15	-	S/N..PROB.C		
		24	0	0	0	0	0	0	0	1	1	1	-	S/N..PROB.D		
5	31.0	1 F	2 F	2 F	2 F	2 F	2 F	1 F	2 F	2 F	2 F	2 F	2 F	-	1 F	MODE
		52	159	148	143	141	140	43	146	154	170	186	-	-	47	ANGLE
		50	99	99	99	99	99	99	99	96	70	21	-	-	66	C.PROB.
		96	100	99	98	98	98	96	99	99	100	102	-	-	96	DELAY
		175	161	162	163	164	165	166	168	169	171	172	-	-	175	NOISE
		262	242	243	245	246	248	249	251	254	256	257	-	-	262	FS.LOSS
		4	56	50	44	39	35	18	27	24	21	20	-	-	4	P. LOSS
		25	-31	-24	-19	-14	-9	8	-0	2	5	7	-	-	25	S/N..DB
		99	0	0	2	6	16	90	47	66	77	85	-	-	99	S/N..PROB.A
		98	0	0	0	0	2	44	13	22	30	38	-	-	98	S/N..PROB.B
		77	0	0	0	0	0	11	1	3	5	8	-	-	77	S/N..PROB.C
		29	0	0	0	0	0	1	0	0	0	0	-	-	29	S/N..PROB.D

		OPERATING FREQUENCIES																
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30				
10	29.1	1 F 53 50 96 175 261 4 24 99 98 75 28	2 F 147 99 98 161 241 52 -27 0 0 0 0	2 F 142 99 98 162 243 46 -20 1 0 0 0	2 F 140 99 98 163 245 40 -15 5 0 0 0	2 F 141 99 98 164 246 36 -10 14 25 1 4	2 F 143 99 99 165 248 29 -6 25 36 8 18	2 F 151 99 99 166 251 25 -3 57 36 29	2 F 164 84 100 168 254 22 1 76 57 29	2 F 188 37 102 169 254 20 4 81 66 34	-	-	-	-	-	1 F 43 82 96 174 260 5 23 99 97 70 25	1 F 51 32 96 175 262 4 25 99 98 77 29	MODE ANGLE C.PROB. DELAY NOISE FSLOSS P. LOSS S/N..DB S/N..PROB.A S/N..PROB.B S/N..PROB.C S/N..PROB.D
12	27.4	1 F 53 50 96 174 260 2 25 99 99 80 34	2 F 133 99 98 161 241 33 -8 20 3 8 0 0	2 F 134 99 98 162 243 29 -4 33 3 16 0 0	2 F 136 99 98 163 245 26 0 49 16 21 2 0	2 F 138 99 98 164 246 23 1 60 71 27 3 0	2 F 141 99 98 165 248 22 3 80 89 34 5 0	2 F 145 99 99 166 251 20 5 71 92 43 8 1	2 F 145 99 91 166 251 20 3 89 92 49 13 1	2 F 155 99 99 166 254 18 8 89 92 49 16 2	-	-	-	-	-	1 F 50 56 96 174 260 2 25 99 98 80 33	1 F 52 9 96 175 262 2 27 99 99 84 38	ANGLE C.PROB. DELAY NOISE FSLOSS P. LOSS S/N..DB S/N..PROB.A S/N..PROB.B S/N..PROB.C S/N..PROB.D
14	20.6	1 F 56 50 96 171 255 1 26 99 99 82 35	2 F 145 99 99 161 241 17 7 86 39 11 1	2 F 149 99 99 162 243 16 8 89 44 13 1	2 F 155 98 100 163 245 15 9 92 49 16 2	2 F 156 91 101 164 247 15 10 94 49 16 2	2 F 174 74 102 165 247 15 10 94 54 18 3	2 F 196 47 102 166 250 15 10 94 54 18 3	2 F 196 61 96 169 253 15 25 99 99 80 34	-	-	-	-	-	1 F 41 89 96 169 253 2 25 99 99 81 35	1 F 56 16 96 171 255 1 26 99 99 82 35	MODE ANGLE C.PROB. DELAY NOISE FSLOSS P. LOSS S/N..DB S/N..PROB.A S/N..PROB.B S/N..PROB.C S/N..PROB.D	
16	13.3	1 F 63 5 97 166 248 3 23 99 97 32 67 25	2 F 209 49 104 161 242 18 5 78 32 92 7 0	1 F 41 99 96 96 162 45 19 99 96 94 48 15	1 F 50 84 97 97 163 50 20 99 96 96 54 18	1 F 59 60 97 165 244 4 21 99 97 97 66 21	1 F 63 32 97 166 246 4 22 99 97 97 70 24	1 F 63 32 97 166 249 3 23 99 99 97 70 27	-	-	-	-	-	-	-	MODE ANGLE C.PROB. DELAY NOISE FSLOSS P. LOSS S/N..DB S/N..PROB.A S/N..PROB.B S/N..PROB.C S/N..PROB.D		

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	9.9	1 F	1 F	1 F	1 F	-	-	-	-	-	-	-	-	-	MODE
		76	63	75	75	-	-	-	-	-	-	-	-	-	ANGLE
		50	81	46	15	-	-	-	-	-	-	-	-	-	C.PROB.
		98	97	98	98	-	-	-	-	-	-	-	-	-	DELAY
		162	161	162	163	-	-	-	-	-	-	-	-	-	NOISE
		243	241	243	245	-	-	-	-	-	-	-	-	-	FS.LOSS
		5	6	5	4	-	-	-	-	-	-	-	-	-	P. LOSS
		20	18	20	21	-	-	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	-	-	-	-	-	-	-	-	-	S/N..PROB.A
		93	89	94	95	-	-	-	-	-	-	-	-	-	S/N..PROB.B
		52	44	53	60	-	-	-	-	-	-	-	-	-	S/N..PROB.C
		20	15	20	23	-	-	-	-	-	-	-	-	-	S/N..PROB.D
20	9.9	1 F	1 F	1 F	1 F	-	-	-	-	-	-	-	-	-	MODE
		85	71	84	84	-	-	-	-	-	-	-	-	-	ANGLE
		50	80	47	18	-	-	-	-	-	-	-	-	-	C.PROB.
		98	97	98	98	-	-	-	-	-	-	-	-	-	DELAY
		162	161	162	163	-	-	-	-	-	-	-	-	-	NOISE
		243	241	243	245	-	-	-	-	-	-	-	-	-	FS.LOSS
		5	6	5	4	-	-	-	-	-	-	-	-	-	P. LOSS
		20	19	20	21	-	-	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	-	-	-	-	-	-	-	-	-	S/N..PROB.A
		94	91	94	95	-	-	-	-	-	-	-	-	-	S/N..PROB.B
		53	47	53	60	-	-	-	-	-	-	-	-	-	S/N..PROB.C
		20	17	20	23	-	-	-	-	-	-	-	-	-	S/N..PROB.D
22	11.2	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	-	-	-	-	MODE
		85	63	69	81	85	85	-	-	-	-	-	-	-	ANGLE
		50	96	84	56	27	8	-	-	-	-	-	-	-	C.PROB.
		98	97	97	98	98	98	-	-	-	-	-	-	-	DELAY
		164	161	162	163	164	165	-	-	-	-	-	-	-	NOISE
		245	241	243	245	246	248	-	-	-	-	-	-	-	FS.LOSS
		4	6	5	4	3	3	-	-	-	-	-	-	-	P. LOSS
		22	18	20	21	21	22	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	-	-	-	-	-	-	-	S/N..PROB.A
		96	89	94	95	96	97	-	-	-	-	-	-	-	S/N..PROB.B
		61	44	53	60	60	66	-	-	-	-	-	-	-	S/N..PROB.C
		24	15	20	23	23	26	-	-	-	-	-	-	-	S/N..PROB.D
24	11.6	1 F	1 F	1 F	1 F	1 F	1 F	-	-	-	-	-	-	-	MODE
		81	57	63	71	80	80	-	-	-	-	-	-	-	ANGLE
		50	93	82	63	37	13	-	-	-	-	-	-	-	C.PROB.
		98	97	97	97	98	98	-	-	-	-	-	-	-	DELAY
		164	161	162	163	164	165	-	-	-	-	-	-	-	NOISE
		246	241	243	245	246	248	-	-	-	-	-	-	-	FS.LOSS
		4	6	5	4	3	3	-	-	-	-	-	-	-	P. LOSS
		21	18	19	20	21	22	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	-	-	-	-	-	-	-	S/N..PROB.A
		95	89	92	94	96	97	-	-	-	-	-	-	-	S/N..PROB.B
		58	43	48	54	60	66	-	-	-	-	-	-	-	S/N..PROB.C
		20	13	15	18	21	24	-	-	-	-	-	-	-	S/N..PROB.D

[REDACTED]

1 DEC SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C RCVR 0 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0dB(A), 10dB(B), 20dB(C), 30dB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	88	82	48	12	10	94	85	60	20	18	84	76	42	15
4	98	84	64	26	12	98	74	52	20	20	84	79	45	18
6	94	54	34	12	14	99	96	80	36	22	99	94	54	22
8	97	81	57	20	16	99	99	72	30	24	98	94	62	20

[REDACTED]

2	DEC	SSN=	110	26.015
TRANSMITTER SITÉ C	RECEIVER RCVR 50	AZIMUTHS 61.0 262.8	N.MILES 1493.7	
SIGMA= 1000 SQ. METERS				ANT= 25DB
OFF AZIMUTH 0 DEG.	MIN. ANGLE= 4 DEG.	OFF AZIMUTH 0 DEG.		
PWR=200.00KW	3 MC/S MAN.NOISE= -148 DBW	REQ.S/N= 0, 10, 20, 30DB		
OPERATING FREQUENCIES				
GMT	MUF	9 10 11 12 13 14 16 18 20 22 24 27 30		
2	10.9	1F- 1F- 1F- 1F- - - - - - - -	- - - - - - -	MODE
		64 45 52 63 63 - - - - - - -	- - - - - - -	ANGLE
		5 88 72 48 19 - - - - - - -	- - - - - - -	C.PROB.
		97 96 96 97 97 - - - - - - -	- - - - - - -	DELAY
		163 161 162 163 164 - - - - - - -	- - - - - - -	NOISE
		244 241 243 245 246 - - - - - - -	- - - - - - -	FS.LOSS
		4 6 5 4 4 - - - - - - -	- - - - - - -	P. LOSS
		20 18 19 20 21 - - - - - - -	- - - - - - -	S/N..DB
		99 99 99 99 99 - - - - - - -	- - - - - - -	S/N..PROB.A
		94 89 92 94 96 - - - - - - -	- - - - - - -	S/N..PROB.B
		54 43 48 54 60 - - - - - - -	- - - - - - -	S/N..PROB.C
		18 13 15 18 21 - - - - - - -	- - - - - - -	S/N..PROB.D
4	22.4	1F- 2F- 2F- 2F- 2F- 1F+ 1F+ 1F+ 1F+ 1F- 1F- -	- - - - - - -	MODE
		43 134 137 141 146 153 41 46 52 64 40 42 -	- - - - - - -	ANGLE
		50 99 99 99 97 89 99 98 86 54 57 24 -	- - - - - - -	C.PROB.
		96 98 98 98 99 99 96 96 97 96 96 96 -	- - - - - - -	DELAY
		172 161 162 163 164 165 166 168 169 171 172 173 -	- - - - - - -	NOISE
		257 241 243 245 246 248 249 251 253 255 256 258 -	- - - - - - -	FS.LOSS
		2 24 21 20 18 17 9 8 7 7 2 2 -	- - - - - - -	P. LOSS
		25 0 3 5 6 8 17 19 19 20 25 26 -	- - - - - - -	S/N..DB
		99 52 70 80 84 90 99 99 99 99 99 99 -	- - - - - - -	S/N..PROB.A
		98 17 26 34 38 45 87 91 92 93 98 99 -	- - - - - - -	S/N..PROB.B
		78 2 5 8 10 14 41 47 49 50 78 82 -	- - - - - - -	S/N..PROB.C
		33 0 0 0 1 2 11 15 16 16 32 36 -	- - - - - - -	S/N..PROB.D
6	30.6	1F+ 2F- 2F- 1F+ 1F+ 2F- 2F- 2F- 2F- 2F- 1F+ 1F+ -	- - - - - - -	MODE
		59 138 129 125 50 42 124 127 132 141 157 168 45 56 -	- - - - - - -	ANGLE
		50 99 99 99 99 99 99 98 87 61 27 88 58 -	- - - - - - -	C.PROB.
		97 98 98 97 96 96 97 97 98 98 99 100 96 96 -	- - - - - - -	DELAY
		175 161 162 163 164 165 166 168 169 171 172 173 174 175 -	- - - - - - -	NOISE
		262 241 243 245 246 247 249 251 253 255 257 259 260 262 -	- - - - - - -	FS.LOSS
		8 47 42 37 21 19 27 23 20 19 17 17 8 8 -	- - - - - - -	P. LOSS
		21 -22 -17 -12 4 6 -1 3 6 9 10 10 20 21 -	- - - - - - -	S/N..DB
		99 0 3 9 76 84 44 69 84 90 93 93 99 99 -	- - - - - - -	S/N..PROB.A
		94 0 0 0 29 36 11 24 36 46 51 51 94 94 -	- - - - - - -	S/N..PROB.B
		55 0 0 0 5 8 1 4 8 12 15 15 54 55 -	- - - - - - -	S/N..PROB.C
		17 0 0 0 0 0 0 0 1 1 1 1 16 17 -	- - - - - - -	S/N..PROB.D
8	29.5	1F+ 2F- 2F- 2F- 2F- 1F+ 1F+ 2F- 2F- 1F+ 1F+ 1F+ -	- - - - - - -	MODE
		63 155 142 135 132 131 49 40 141 153 41 44 52 62 -	- - - - - - -	ANGLE
		50 99 99 99 99 99 99 98 82 99 99 86 40 -	- - - - - - -	C.PROB.
		97 99 98 98 98 98 96 96 98 99 96 96 96 97 -	- - - - - - -	DELAY
		175 161 162 163 164 165 166 168 169 171 172 173 174 175 -	- - - - - - -	NOISE
		262 241 243 245 246 248 249 251 253 255 256 258 260 262 -	- - - - - - -	FS.LOSS
		9 56 50 45 40 36 21 17 24 21 11 10 9 9 -	- - - - - - -	P. LOSS
		19 -31 -25 -19 -14 -10 4 9 2 6 17 18 19 20 -	- - - - - - -	S/N..DB
		99 0 0 2 6 14 75 91 66 81 99 99 99 99 -	- - - - - - -	S/N..PROB.A
		92 0 0 0 0 1 29 47 22 34 85 88 92 93 -	- - - - - - -	S/N..PROB.B
		49 0 0 0 0 0 5 13 3 7 38 42 48 50 -	- - - - - - -	S/N..PROB.C
		14 0 0 0 0 0 0 1 0 0 8 10 13 14 -	- - - - - - -	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30		
10	30.6	1F-	2F-	2F-	1F+	1F+	1F+	2F-	2F-	1F+	1F+	1F+	1F+	1F+	MODE	
		40	141	134	131	53	45	40	139	149	41	44	48	60	63	ANGLE
		50	99	99	99	99	99	99	92	99	99	95	62	11	C.PROB.	
		96	98	98	98	96	96	96	98	99	96	96	97	97	DELAY	
		175	161	162	163	164	165	166	168	169	171	172	173	174	175	NOISE
		262	241	243	245	246	247	249	251	253	255	256	258	260	262	FSLOSS
		4	53	47	41	24	21	19	25	22	11	10	10	9	8	P. LOSS
		25	-28	-21	-16	1	4	7	1	4	16	17	18	19	20	S/N..DB
		99	0	1	4	60	76	87	57	76	99	99	99	99	99	S/N..PROB.A
		98	0	0	0	19	29	40	18	29	81	85	88	92	93	S/N..PROB.B
		77	0	0	0	2	5	9	2	5	34	38	42	48	50	S/N..PROB.C
		29	0	0	0	0	0	0	0	0	7	8	10	13	14	S/N..PROB.D
12	28.9	1F-	2F-	1F+	1F+	1F+	1F+	1F+	- MODE							
		40	124	124	126	127	130	133	142	158	41	46	52	64	-	ANGLE
		50	99	99	99	99	99	95	73	99	94	79	32	-	C.PROB.	
		96	97	97	97	98	98	98	98	99	96	96	97	-	DELAY	
		175	161	162	163	164	165	166	168	169	171	172	173	174	-	NOISE
		261	241	243	245	246	248	249	251	254	255	256	258	260	-	FSLOSS
		2	33	29	26	24	22	20	18	17	8	7	7	7	-	P. LOSS
		26	-8	-4	-1	1	3	5	8	9	20	20	21	20	-	S/N..DB
		99	20	33	45	60	71	80	89	92	99	99	99	99	-	S/N..PROB.A
		99	3	8	13	21	27	34	43	49	93	93	95	94	-	S/N..PROB.B
		83	0	0	2	3	5	8	13	16	50	51	57	54	-	S/N..PROB.C
		36	0	0	0	0	0	0	1	2	16	17	20	18	-	S/N..PROB.D
14	21.7	1F-	2F-	2F-	2F-	2F-	1F+	1F+	1F+	1F+	1F-	1F-	-	-	MODE	
		44	134	138	143	149	159	42	47	55	67	44	44	-	-	ANGLE
		50	99	99	99	95	82	99	96	79	38	41	6	-	-	C.PROB.
		96	98	98	99	100	96	96	96	97	96	96	-	-	DELAY	
		172	161	162	163	164	165	166	168	169	171	172	173	-	-	NOISE
		256	241	243	245	246	248	249	251	253	255	256	258	-	-	FSLOSS
		1	17	16	15	15	14	6	6	6	7	1	1	-	-	P. LOSS
		27	7	8	9	10	10	19	20	20	21	26	27	-	-	S/N..DB
		99	86	89	92	94	94	99	99	99	99	99	99	-	-	S/N..PROB.A
		99	39	44	49	55	54	92	93	94	94	99	99	-	-	S/N..PROB.B
		85	11	13	16	18	18	49	52	54	56	82	85	-	-	S/N..PROB.C
		38	1	1	2	3	3	16	17	18	19	35	39	-	-	S/N..PROB.D
16	14.0	1F-	1F+	1F+	1F+	1F+	1F-	1F-	-	-	-	-	-	-	MODE	
		52	49	53	58	65	42	52	52	-	-	-	-	-	ANGLE	
		50	99	98	91	71	77	51	10	-	-	-	-	-	-	C.PROB.
		96	96	97	97	96	96	96	96	-	-	-	-	-	DELAY	
		166	161	162	163	164	165	166	168	-	-	-	-	-	-	NOISE
		249	241	243	244	246	247	249	251	-	-	-	-	-	-	FSLOSS
		3	10	9	9	9	3	3	2	-	-	-	-	-	-	P. LOSS
		23	14	15	16	16	22	23	24	-	-	-	-	-	-	S/N..DB
		99	98	98	99	99	99	99	99	-	-	-	-	-	-	S/N..PROB.A
		97	74	79	84	84	97	97	98	-	-	-	-	-	-	S/N..PROB.B
		71	29	33	37	38	66	70	74	-	-	-	-	-	-	S/N..PROB.C
		27	6	8	10	10	24	27	29	-	-	-	-	-	-	S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	10.4	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	-	-	MODE
		65	49	59	64	64	-	-	-	-	-	-	-	-	ANGLE
		50	90	63	28	7	-	-	-	-	-	-	-	-	C.PROB.
		97	96	97	97	97	-	-	-	-	-	-	-	-	DELAY
		163	161	162	163	164	-	-	-	-	-	-	-	-	NOISE
		244	241	243	245	246	-	-	-	-	-	-	-	-	FS.LOSS
		5	6	5	4	4	-	-	-	-	-	-	-	-	P. LOSS
		20	18	19	20	21	-	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	-	-	-	-	-	-	-	-	S/N..PROB.A
		93	89	92	94	96	-	-	-	-	-	-	-	-	S/N..PROB.B
		50	44	48	54	60	-	-	-	-	-	-	-	-	S/N..PROB.C
		19	15	18	21	23	-	-	-	-	-	-	-	-	S/N..PROB.D
20	10.4	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	-	-	MODE
		74	57	67	73	73	-	-	-	-	-	-	-	-	ANGLE
		50	89	63	30	9	-	-	-	-	-	-	-	-	C.PROB.
		97	97	97	97	97	-	-	-	-	-	-	-	-	DELAY
		163	161	162	163	164	-	-	-	-	-	-	-	-	NOISE
		244	241	243	245	246	-	-	-	-	-	-	-	-	FS.LOSS
		4	6	5	4	3	-	-	-	-	-	-	-	-	P. LOSS
		21	18	20	20	21	-	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	-	-	-	-	-	-	-	-	S/N..PROB.A
		94	89	94	94	96	-	-	-	-	-	-	-	-	S/N..PROB.B
		56	44	53	54	60	-	-	-	-	-	-	-	-	S/N..PROB.C
		21	15	20	21	23	-	-	-	-	-	-	-	-	S/N..PROB.D
22	11.7	1F-	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	-	MODE
		74	51	56	64	74	74	-	-	-	-	-	-	-	ANGLE
		50	98	91	71	41	17	-	-	-	-	-	-	-	C.PROB.
		98	96	96	97	97	97	-	-	-	-	-	-	-	DELAY
		164	161	162	163	164	165	-	-	-	-	-	-	-	NOISE
		246	241	243	245	246	248	-	-	-	-	-	-	-	FS.LOSS
		4	6	5	4	3	3	-	-	-	-	-	-	-	P. LOSS
		21	18	19	20	21	22	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	-	-	-	-	-	-	-	S/N..PROB.A
		95	89	92	94	96	97	-	-	-	-	-	-	-	S/N..PROB.B
		59	44	48	54	60	66	-	-	-	-	-	-	-	S/N..PROB.C
		22	15	18	21	23	26	-	-	-	-	-	-	-	S/N..PROB.D
24	12.1	1F-	1F-	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	MODE
		70	46	50	56	67	69	69	-	-	-	-	-	-	ANGLE
		50	96	88	74	53	26	8	-	-	-	-	-	-	C.PROB.
		97	96	96	96	97	97	97	-	-	-	-	-	-	DELAY
		164	161	162	163	164	165	166	-	-	-	-	-	-	NOISE
		246	241	243	244	246	248	249	-	-	-	-	-	-	FS.LOSS
		6	5	4	4	3	3	-	-	-	-	-	-	-	P. LOSS
		22	18	19	20	21	22	23	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	99	99	-	-	-	-	-	-	S/N..PROB.A
		96	89	92	94	96	97	97	-	-	-	-	-	-	S/N..PROB.B
		61	43	48	54	60	66	70	-	-	-	-	-	-	S/N..PROB.C
		21	13	15	18	21	24	27	-	-	-	-	-	-	S/N..PROB.D

2
TRANSMITTER DEC SSN= 110 26.015
SITE C RECEIVER AZIMUTHS N.MILES
 RCVR 50 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0DB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	94	89	55	20	10	99	97	63	18	18	93	86	49	19
4	99	98	74	30	12	99	99	76	30	20	92	86	49	19
6	98	99	53	15	14	99	99	73	32	22	99	97	58	24
8	99	97	60	20	16	99	95	71	29	24	99	96	62	24

3 DEC SSN= 110 26.015
 TRANSMITTER RECEIVER AZIMUTHS N.MILES
 SITE C RCVR 100 61.0 262.8 1493.7
 SIGMA= 1000 SQ. METERS
 OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
 PWR=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB
 OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30
2	11.5	1F+	1F+	1F-	1F-	1F-	-	-	-	-	-	-	-	-
		53	86	96	46	52	52	-	-	-	-	-	-	-
		50	66	34	61	34	11	-	-	-	-	-	-	-
		94	98	99	94	94	94	-	-	-	-	-	-	-
		164	161	162	163	164	165	-	-	-	-	-	-	-
		245	241	243	244	246	247	-	-	-	-	-	-	-
		2	12	11	2	2	2	-	-	-	-	-	-	-
		24	13	13	23	23	24	-	-	-	-	-	-	-
		99	97	97	99	99	99	-	-	-	-	-	-	-
		98	69	70	97	97	98	-	-	-	-	-	-	-
		73	26	26	71	71	76	-	-	-	-	-	-	-
		29	5	5	27	27	30	-	-	-	-	-	-	-
4	19.3	1F+												
		77	48	48	48	49	51	53	58	66	77	77	-	-
		50	99	99	99	99	99	99	95	74	36	8	-	-
		98	96	96	96	96	96	97	97	98	98	98	-	-
		170	161	162	163	164	165	166	168	169	171	172	-	-
		254	241	243	244	246	247	249	251	253	255	257	-	-
		8	15	13	12	11	10	9	8	8	8	8	-	-
		18	10	12	13	14	16	16	18	18	19	20	-	-
		99	93	96	97	98	99	99	99	99	99	99	-	-
		89	52	65	71	76	84	84	89	90	90	93	-	-
		44	17	23	27	31	38	37	43	45	46	51	-	-
		13	2	4	5	7	10	10	13	13	14	17	-	-
6	29.1	1F+	2F-	2F-	1F+									
		71	133	122	117	58	50	47	44	44	46	48	52	60
		50	99	99	99	99	99	99	99	99	99	96	77	39
		97	98	97	97	97	96	96	96	96	96	96	97	97
		175	161	162	163	164	165	166	168	169	171	172	173	174
		262	241	243	245	246	247	249	251	253	255	256	258	260
		9	38	34	38	21	19	17	14	12	11	10	9	8
		19	-13	-9	-5	4	6	9	12	14	17	18	19	20
		99	7	16	29	76	84	92	96	98	99	99	99	99
		92	0	2	5	29	36	48	63	76	85	88	91	92
		48	0	0	0	5	8	14	21	29	37	42	47	48
		13	0	0	0	0	1	3	5	8	10	13	13	14
8	28.1	1F+	2F+	2F-	2F-	2F-	1F+							
		75	169	137	128	123	64	57	50	49	50	53	57	68
		50	99	99	99	99	99	99	99	99	99	97	69	17
		98	100	98	97	97	97	96	96	96	96	97	97	97
		175	161	162	163	164	165	166	168	169	171	172	173	174
		261	242	243	245	246	247	249	251	253	255	256	258	260
		10	65	41	36	33	24	21	17	15	13	12	11	10
		18	-40	-15	-11	-7	2	4	9	12	15	16	17	18
		99	0	5	11	22	66	75	91	97	98	99	99	99
		88	0	0	1	3	42	29	47	66	77	82	85	90
		42	0	0	0	0	3	5	13	22	30	34	38	45
		10	0	0	0	0	0	1	3	5	7	9	11	12

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
10	26.4	1F+	2F-	2F-	1F+	- MODE									
		76	135	126	122	60	53	50	49	50	52	56	62	75	- ANGLE
		5	99	99	99	99	99	99	99	99	99	98	88	37	- C.PROB.
		98	98	97	97	97	96	96	96	96	96	96	97	98	- DELAY
		174	161	162	163	164	165	166	168	169	171	172	173	174	- NOISE
		260	241	243	245	246	247	249	251	253	255	257	258	260	- FS.LOSS
		16	43	38	34	24	21	19	16	14	12	11	10	10	- P. LOSS
		18	-17	-12	-8	1	4	6	11	13	16	17	18	18	- S/N..DB
		99	3	9	19	60	76	84	95	97	99	99	99	99	- S/N..PROB.A
		89	0	0	2	19	29	36	57	71	81	85	88	90	- S/N..PROB.B
		43	0	0	0	2	5	8	18	25	34	38	42	44	- S/N..PROB.C
		11	0	0	0	0	0	2	4	7	8	10	11	-	- S/N..PROB.D
12	24.9	1F+	- MODE												
		76	46	44	43	43	44	44	46	49	53	59	68	75	- ANGLE
		50	99	99	99	99	99	99	99	97	88	64	12	- C.PROB.	
		98	96	96	96	96	96	96	96	96	97	97	98	- DELAY	
		173	161	162	163	164	165	166	168	169	171	172	173	174	- NOISE
		259	241	243	244	246	247	249	251	253	255	257	258	260	- FS.LOSS
		8	22	18	16	14	13	12	10	9	8	8	8	8	- P. LOSS
		19	3	6	9	11	12	14	16	17	19	20	20	20	- S/N..DB
		99	69	83	92	96	97	98	99	99	99	99	99	99	- S/N..PROB.A
		92	26	37	49	60	66	75	82	87	90	93	93	94	- S/N..PROB.B
		49	5	9	16	21	24	30	36	41	46	51	51	54	- S/N..PROB.C
		16	0	1	2	3	4	7	9	11	14	17	17	18	- S/N..PROB.D
14	18.7	1F+	-	-	-	-	- MODE								
		78	45	46	47	49	51	53	60	71	78	-	-	-	- ANGLE
		50	99	99	99	99	99	99	92	65	16	-	-	-	- C.PROB.
		98	96	96	96	96	96	96	97	97	98	-	-	-	- DELAY
		17	161	162	163	164	165	166	168	169	171	-	-	-	- NOISE
		254	241	243	244	246	247	249	251	253	255	-	-	-	- FS.LOSS
		7	10	9	8	8	7	7	7	7	7	-	-	-	- P. LOSS
		19	15	16	17	17	18	19	20	19	20	-	-	-	- S/N..DB
		99	98	99	99	99	99	99	99	99	99	-	-	-	- S/N..PROB.A
		91	78	83	87	87	90	92	93	92	93	-	-	-	- S/N..PROB.B
		47	32	37	41	41	45	49	52	49	50	-	-	-	- S/N..PROB.C
		14	7	9	11	12	14	16	17	16	16	-	-	-	- S/N..PROB.D
16	14.8	1F-	1F+	1F+	1F+	1F+	1F+	-	-	-	-	-	-	-	- MODE
		40	61	65	71	82	85	85	-	-	-	-	-	-	- ANGLE
		5	99	96	83	56	27	8	-	-	-	-	-	-	- C.PROB.
		93	97	97	97	98	98	98	-	-	-	-	-	-	- DELAY
		167	161	162	163	164	165	166	-	-	-	-	-	-	- NOISE
		249	241	243	245	246	248	249	-	-	-	-	-	-	- FS.LOSS
		1	11	10	9	9	9	9	-	-	-	-	-	-	- P. LOSS
		25	14	15	15	15	16	17	-	-	-	-	-	-	- S/N..DB
		99	98	98	99	99	99	99	-	-	-	-	-	-	- S/N..PROB.A
		98	74	79	80	80	84	87	-	-	-	-	-	-	- S/N..PROB.B
		78	29	33	34	34	38	41	-	-	-	-	-	-	- S/N..PROB.C
		32	6	8	8	8	10	11	-	-	-	-	-	-	- S/N..PROB.D

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	10.9	1F+	1F-	1F-	1F-	-	-	-	-	-	-	-	-	-	MODE
		53	95	43	53	53	-	-	-	-	-	-	-	-	ANGLE
		50	53	79	46	17	-	-	-	-	-	-	-	-	C.PROB.
		94	99	94	94	94	-	-	-	-	-	-	-	-	DELAY
		163	161	162	163	164	-	-	-	-	-	-	-	-	NOISE
		244	241	242	244	246	-	-	-	-	-	-	-	-	FS.LOSS
		2	12	3	2	2	-	-	-	-	-	-	-	-	P. LOSS
		23	12	22	23	23	-	-	-	-	-	-	-	-	S/N..DB
		99	96	99	99	99	-	-	-	-	-	-	-	-	S/N..PROB.A
		97	63	96	97	97	-	-	-	-	-	-	-	-	S/N..PROB.B
		70	25	65	71	71	-	-	-	-	-	-	-	-	S/N..PROB.C
		29	6	25	29	29	-	-	-	-	-	-	-	-	S/N..PROB.D
20	10.9	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	-	-	MODE
		63	44	51	62	62	-	-	-	-	-	-	-	-	ANGLE
		50	94	77	46	19	-	-	-	-	-	-	-	-	C.PROB.
		95	94	94	95	95	-	-	-	-	-	-	-	-	DELAY
		163	161	162	163	164	-	-	-	-	-	-	-	-	NOISE
		244	240	242	244	246	-	-	-	-	-	-	-	-	FS.LOSS
		2	3	3	2	2	-	-	-	-	-	-	-	-	P. LOSS
		23	22	22	23	23	-	-	-	-	-	-	-	-	S/N..DB
		99	99	99	99	99	-	-	-	-	-	-	-	-	S/N..PROB.A
		97	96	96	97	97	-	-	-	-	-	-	-	-	S/N..PROB.B
		70	63	65	71	71	-	-	-	-	-	-	-	-	S/N..PROB.C
		28	25	25	29	29	-	-	-	-	-	-	-	-	S/N..PROB.D
22	12.3	1F-	1F+	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	MODE
		63	87	43	49	59	62	62	-	-	-	-	-	-	ANGLE
		50	88	95	83	58	30	11	-	-	-	-	-	-	C.PROB.
		95	98	94	94	94	95	95	-	-	-	-	-	-	DELAY
		165	161	162	163	164	165	166	-	-	-	-	-	-	NOISE
		246	241	242	244	246	247	248	-	-	-	-	-	-	FS.LOSS
		2	12	3	2	2	2	1	-	-	-	-	-	-	P. LOSS
		24	12	22	23	23	24	25	-	-	-	-	-	-	S/N..DB
		99	96	99	99	99	99	99	-	-	-	-	-	-	S/N..PROB.A
		98	63	96	97	97	98	98	-	-	-	-	-	-	S/N..PROB.B
		72	25	65	71	71	76	80	-	-	-	-	-	-	S/N..PROB.C
		30	6	25	29	29	32	35	-	-	-	-	-	-	S/N..PROB.D
24	12.7	1F-	1F+	1F-	1F-	1F-	1F-	-	-	-	-	-	-	-	MODE
		58	81	90	42	49	58	58	-	-	-	-	-	-	ANGLE
		50	86	67	82	65	42	18	-	-	-	-	-	-	C.PROB.
		94	98	99	93	94	94	94	-	-	-	-	-	-	DELAY
		165	161	162	163	164	165	166	-	-	-	-	-	-	NOISE
		247	241	243	244	246	247	248	-	-	-	-	-	-	FS.LOSS
		2	11	11	2	2	2	1	-	-	-	-	-	-	P. LOSS
		24	13	13	23	23	24	25	-	-	-	-	-	-	S/N..DB
		99	97	97	99	99	99	99	-	-	-	-	-	-	S/N..PROB.A
		98	69	70	97	97	98	98	-	-	-	-	-	-	S/N..PROB.B
		75	26	26	71	71	76	80	-	-	-	-	-	-	S/N..PROB.C
		3	5	5	27	27	30	34	-	-	-	-	-	-	S/N..PROB.D

[REDACTED]

3 DEC SSN= 110 26.015
TRANSMITTER RECEIVER AZIMUTHS N.MILES
SITE C RCVR 100 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0dB(A), 10dB(B), 20dB(C), 30dB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	86	81	59	22	10	99	98	62	16	18	82	81	57	24
4	99	99	69	25	12	99	99	77	27	20	97	96	74	34
6	99	99	73	24	14	99	99	80	34	22	98	97	78	37
8	99	98	66	15	16	99	88	45	16	24	97	96	79	36

4 DEC SSN= 110 26.015

TRANSMITTER SITÉ C	RECEIVER RCVR 150	AZIMUTHS 61.0 262.8	N.MILES 1493.7
-----------------------	----------------------	------------------------	-------------------

SIGMA= 1000 SQ. METERS
OFF AZIMUTH 0 DEG. MIN. ANGLE= 4 DEG. OFF AZIMUTH 0 DEG.
PWR=200.00KW 3 MC/S MAN.NOISE= -148 DBW REQ.S/N= 0, 10, 20, 30DB

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30
2	12.1	1F+	1F+	-	-	-	-	-	-	-	-	-	-	-
	40	101	107	-	-	-	-	-	-	-	-	-	-	-
	50	56	22	-	-	-	-	-	-	-	-	-	-	-
	93	99	100	-	-	-	-	-	-	-	-	-	-	-
	164	161	162	-	-	-	-	-	-	-	-	-	-	-
	246	241	243	-	-	-	-	-	-	-	-	-	-	-
	2	12	12	-	-	-	-	-	-	-	-	-	-	-
	23	12	12	-	-	-	-	-	-	-	-	-	-	-
	99	96	96	-	-	-	-	-	-	-	-	-	-	-
	98	63	65	-	-	-	-	-	-	-	-	-	-	-
	72	23	23	-	-	-	-	-	-	-	-	-	-	-
	28	4	4	-	-	-	-	-	-	-	-	-	-	-
4	18.5	1F+	-	-	-	-	-							
	88	58	59	60	62	64	70	82	87	-	-	-	-	-
	50	99	99	99	99	99	91	60	21	-	-	-	-	-
	98	97	97	97	97	97	97	98	98	-	-	-	-	-
	17	161	162	163	164	165	166	168	169	171	-	-	-	-
	254	241	243	244	246	247	249	251	253	255	-	-	-	-
	9	15	13	12	11	10	10	9	9	9	-	-	-	-
	18	9	11	13	14	15	16	17	17	18	-	-	-	-
	99	91	95	97	98	99	99	99	99	99	-	-	-	-
	88	47	59	71	76	80	84	86	87	88	-	-	-	-
	42	15	20	27	31	34	37	39	41	42	-	-	-	-
	12	2	3	5	7	8	10	11	11	12	-	-	-	-
6	27.8	1F+	2F-	2F-	1F+									
	81	130	116	109	64	59	56	54	55	57	60	64	76	81
	50	99	99	99	99	99	99	99	99	99	98	91	62	22
	98	98	97	96	97	97	96	96	96	96	97	97	98	98
	17	161	162	163	164	165	166	168	169	171	172	173	174	175
	26	241	243	244	246	247	249	251	253	255	257	258	260	262
	9	38	35	31	21	19	17	14	12	11	10	10	9	9
	19	-13	-9	-5	4	6	8	12	14	16	17	18	18	20
	99	7	16	29	76	84	90	96	98	99	99	99	99	99
	91	0	2	5	29	36	44	63	76	81	85	88	90	93
	46	0	0	0	5	8	11	21	29	34	38	42	44	50
	12	0	0	0	0	1	3	5	7	8	10	11	14	S/N..PROB.D
8	26.9	1F+	2F+	2F-	2F-	1F+	-							
	86	176	132	121	115	70	64	60	60	62	65	70	85	-
	50	99	99	99	99	99	99	99	99	99	99	92	48	-
	98	1	1	98	97	97	97	97	97	97	97	97	98	-
	17	161	162	163	164	165	166	168	169	171	172	173	174	-
	26	242	243	245	246	248	249	251	253	255	257	258	260	-
	11	64	41	37	33	23	21	18	15	13	12	11	11	-
	17	-39	-16	-11	-7	2	4	9	11	14	15	16	17	-
	99	0	4	11	22	66	75	91	95	98	98	99	99	-
	87	0	0	1	3	22	29	47	60	72	78	82	87	-
	40	0	0	0	0	3	5	13	19	26	30	34	40	-
	9	0	0	0	0	0	0	1	2	4	6	7	9	-

		OPERATING FREQUENCIES																
GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30				
10	25.3	1F+	2F-	1F+	-	MODE												
		87	130	119	74	66	62	59	59	61	64	69	78	86	-	ANGLE		
		50	99	99	99	99	99	99	99	99	99	95	74	17	-	C.PROB.		
		98	98	97	97	97	97	97	97	97	97	98	98	98	-	DELAY		
		173	161	162	163	164	165	166	168	169	171	172	173	174	-	NOISE		
		259	241	243	245	246	247	249	251	253	255	257	258	260	-	FS.LOSS		
		11	43	38	27	24	21	19	16	14	12	11	11	10	-	P. LOSS		
		16	-18	-13	-1	1	4	6	10	12	15	16	17	17	-	S/N..DB		
		99	2	8	45	60	76	84	93	97	98	99	99	99	-	S/N..PROB.A		
		84	0	0	11	19	29	36	52	66	77	82	85	87	-	S/N..PROB.B		
		37	0	0	1	2	5	8	15	22	30	34	38	40	-	S/N..PROB.C		
		8	0	0	0	0	0	1	3	5	7	9	9	9	-	S/N..PROB.D		
12	23.9	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	-	MODE		
		87	56	54	53	53	54	55	57	61	66	73	86	-	-	ANGLE		
		50	99	99	99	99	99	99	99	99	95	78	47	-	-	C.PROB.		
		98	96	96	96	96	96	96	97	97	97	97	98	98	-	DELAY		
		173	161	162	163	164	165	166	168	169	171	172	173	173	-	NOISE		
		258	241	243	244	246	247	249	251	253	255	257	258	258	-	FS.LOSS		
		9	22	19	16	15	13	12	11	10	9	9	9	9	-	P. LOSS		
		18	3	6	8	10	12	13	16	17	18	19	18	18	-	S/N..DB		
		99	69	83	90	94	97	97	99	99	99	99	99	99	-	S/N..PROB.A		
		88	26	37	45	55	66	70	82	87	88	91	88	88	-	S/N..PROB.B		
		43	5	9	13	18	24	27	36	41	42	47	43	43	-	S/N..PROB.C		
		12	0	1	2	3	4	5	9	11	12	14	12	12	-	S/N..PROB.D		
14	17.9	1F+	1F+	1F+	1F+	1F+	1F+	1F+	1F+	-	-	-	-	-	-	MODE		
		89	55	56	58	60	62	65	73	89	-	-	-	-	-	ANGLE		
		50	99	99	99	99	99	98	85	47	-	-	-	-	-	C.PROB.		
		98	96	96	97	97	97	97	97	98	-	-	-	-	-	DELAY		
		169	161	162	163	164	165	166	168	169	-	-	-	-	-	NOISE		
		253	241	243	244	246	247	249	251	253	-	-	-	-	-	FS.LOSS		
		8	10	9	9	8	8	8	8	8	-	-	-	-	-	P. LOSS		
		18	14	15	16	17	17	18	19	18	-	-	-	-	-	S/N..DB		
		99	98	98	99	99	99	99	99	99	-	-	-	-	-	S/N..PROB.A		
		9	74	79	84	87	87	90	91	90	-	-	-	-	-	S/N..PROB.B		
		45	29	33	37	41	41	45	47	45	-	-	-	-	-	S/N..PROB.C		
		13	6	8	10	12	12	13	15	13	-	-	-	-	-	S/N..PROB.D		
16	11.7	1F+	1F+	1F+	1F+	1F+	-	-	-	-	-	-	-	-	-	MODE		
		96	72	77	85	95	95	-	-	-	-	-	-	-	-	ANGLE		
		5	99	92	72	40	15	-	-	-	-	-	-	-	-	C.PROB.		
		99	97	98	98	99	99	-	-	-	-	-	-	-	-	DELAY		
		164	161	162	163	164	165	-	-	-	-	-	-	-	-	NOISE		
		246	241	243	245	246	248	-	-	-	-	-	-	-	-	FS.LOSS		
		10	11	10	10	10	10	-	-	-	-	-	-	-	-	P. LOSS		
		15	13	14	14	15	15	-	-	-	-	-	-	-	-	S/N..DB		
		98	97	98	98	99	99	-	-	-	-	-	-	-	-	S/N..PROB.A		
		79	69	75	76	80	80	-	-	-	-	-	-	-	-	S/N..PROB.B		
		33	26	30	30	34	34	-	-	-	-	-	-	-	-	S/N..PROB.C		
		8	5	6	7	8	8	-	-	-	-	-	-	-	-	S/N..PROB.D		

OPERATING FREQUENCIES

GMT	MUF	9	10	11	12	13	14	16	18	20	22	24	27	30	
18	11.5	1F+	1F+	-	1F-	1F-	-	-	-	-	-	-	-	-	MODE
		42	107	107	-	41	41	-	-	-	-	-	-	-	ANGLE
		50	39	9	-	34	11	-	-	-	-	-	-	-	C.PROB.
		93	100	100	-	93	93	-	-	-	-	-	-	-	DELAY
		164	161	162	-	164	165	-	-	-	-	-	-	-	NOISE
		245	242	243	-	245	247	-	-	-	-	-	-	-	FS.LOSS
		2	12	12	-	2	2	-	-	-	-	-	-	-	P. LOSS
		24	12	12	-	24	24	-	-	-	-	-	-	-	S/N..DB
		99	96	96	-	99	99	-	-	-	-	-	-	-	S/N..PROB.A
		98	63	65	-	98	98	-	-	-	-	-	-	-	S/N..PROB.B
		73	25	25	-	76	76	-	-	-	-	-	-	-	S/N..PROB.C
		30	6	6	-	32	32	-	-	-	-	-	-	-	S/N..PROB.D
20	11.4	1F-	1F+	1F+	1F-	1F-	1F-	-	-	-	-	-	-	-	MODE
		51	115	115	45	50	50	-	-	-	-	-	-	-	ANGLE
		50	43	13	64	34	12	-	-	-	-	-	-	-	C.PROB.
		94	100	100	94	94	94	-	-	-	-	-	-	-	DELAY
		164	161	162	163	164	165	-	-	-	-	-	-	-	NOISE
		245	242	244	244	246	247	-	-	-	-	-	-	-	FS.LOSS
		2	13	12	2	2	2	-	-	-	-	-	-	-	P. LOSS
		24	11	12	23	23	24	-	-	-	-	-	-	-	S/N..DB
		99	95	96	99	99	99	-	-	-	-	-	-	-	S/N..PROB.A
		98	58	65	97	97	98	-	-	-	-	-	-	-	S/N..PROB.B
		73	22	25	71	71	76	-	-	-	-	-	-	-	S/N..PROB.C
		30	5	6	29	29	32	-	-	-	-	-	-	-	S/N..PROB.D
22	12.9	1F-	1F+	1F+	1F+	1F-	1F-	1F-	-	-	-	-	-	-	MODE
		51	100	116	116	42	51	51	-	-	-	-	-	-	ANGLE
		50	81	49	19	74	47	23	-	-	-	-	-	-	C.PROB.
		94	99	100	100	93	94	94	-	-	-	-	-	-	DELAY
		165	161	162	163	164	165	166	-	-	-	-	-	-	NOISE
		247	241	244	245	245	247	248	-	-	-	-	-	-	FS.LOSS
		2	12	12	11	2	2	1	-	-	-	-	-	-	P. LOSS
		24	12	12	13	23	24	25	-	-	-	-	-	-	S/N..DB
		99	96	96	97	99	99	99	-	-	-	-	-	-	S/N..PROB.A
		98	63	65	71	97	98	98	-	-	-	-	-	-	S/N..PROB.B
		73	25	25	29	71	76	80	-	-	-	-	-	-	S/N..PROB.C
		32	6	6	7	29	32	35	-	-	-	-	-	-	S/N..PROB.D
24	13.4	1F-	1F+	1F+	1F+	1F+	1F-	1F-	-	-	-	-	-	-	MODE
		46	93	105	112	112	42	46	-	-	-	-	-	-	ANGLE
		50	80	57	26	6	58	34	-	-	-	-	-	-	C.PROB.
		94	99	100	100	100	93	94	-	-	-	-	-	-	DELAY
		166	161	162	163	164	165	166	-	-	-	-	-	-	NOISE
		247	241	243	245	247	247	248	-	-	-	-	-	-	FS.LOSS
		2	12	11	11	11	2	1	-	-	-	-	-	-	P. LOSS
		25	12	12	13	14	24	25	-	-	-	-	-	-	S/N..DB
		99	96	96	97	98	99	99	-	-	-	-	-	-	S/N..PROB.A
		98	63	65	71	76	98	98	-	-	-	-	-	-	S/N..PROB.B
		77	23	23	27	31	76	80	-	-	-	-	-	-	S/N..PROB.C
		32	4	4	5	7	30	34	-	-	-	-	-	-	S/N..PROB.D

4
TRANSMITTER DEC SSN= 110 26.015
SITE C RECEIVER AZIMUTHS N.MILES
 RCVR 150 61.0 262.8 1493.7

TOTAL RELIABILITY(T.REL.)

REQ. S/N= 0DB(A), 10DB(B), 20DB(C), 30DB(D)

GMT	A	B	C	D	GMT	A	B	C	D	GMT	A	B	C	D
2	54	49	36	14	10	99	94	52	11	18	60	50	37	15
4	99	99	67	21	12	99	99	73	26	20	82	76	55	24
6	99	99	65	20	14	99	99	73	27	22	95	90	70	31
8	99	95	50	12	16	99	79	38	9	24	91	79	55	21